Government of India

Central Waterways, Irrigation and Navigation Research Station, Poona.

Director
K. K. FRAMJI, M. B. E., I. S. E.

RESEARCH PUBLICATION No. 12

ANNUAL REPORT (TECHNICAL) OF WORK DONE

DURING THE YEAR 1947

AND INDEX FOR 1943-1947.

BY

K. K. FRAMJI, M. B. E., B. A. (Bom.), B. Sc. (Lond.), A. K. C. (Lond.), A. M. Am. S. C. E., M. I. E., I. S. E., Rao Bahadur D. V. JOGLEKAR, B. E., Deputy Director

STAFF AT KHADAKVASLA



PRINTED AT CHITRASHALA PRESS POONA 1948

Sale Price :- Rs. 25|- or 38sh. 6d.

D2.2,84

Government of India

Central Waterways, Irrigation and Navigation Research Station, Poons.

Director:
K. K. FRAMJI, M. B. E., I. S. E.

RESEARCH PUBLICATION No. 12

ANNUAL REPORT (TECHNICAL) OF WORK DONE

DURING THE YEAR 1947

AND INDEX FOR 1943-1947.

BY

K. K. FRAMJI, M. B. E., B. A. (Bom.), B. Sc. (Lond.), A. K. C. (Lond.), A. M. Am. S. C. E., M. I. E., I. S. E.,

Rao Bahadur D. V. JOGLEKAR, B. E.,

Deputy Director

AND

STAFF AT KHADAKVASLA



List of Research Publications of the Central Waterways, Irrigation and Navigation Research
Station, Poona, available for Sale with the Manager of Publications, Delhi, and Agents.

Symbol No.			E			Year of Publica- tion.	
			Rs	. А.	P.		
1HR. 1.38	1	Annual Report of work done during 1937-38 by C. C. Inglis, A. R. Thomas, Rao Sahib D.V. Joglekar and staff at Khadakvasla.	91-032	8	0	1939	
IHR, 1.30	2	Annual Report of work done during 1938-'39 by same authors as in 1.	7	8	0	1940	
IHR. 2	3	Note on the theory, design and construction of Gibb Modules, which, without moving parts, give a constant discharge within working limits irrespective of variations in upstream and downstream water levels by C. C. Inglis, and Rao Sahib D. V. Joglekar.	3	0	0	1941	
IHR. 1.40	4	Annual Report of work done during 1939-'40 by C. C. Inglis, A. R. Thomas, Rao Sahib D. V. Joglekar and staff at Khadakvasla.	7	8	0.	1941	
IHR. 1.41	5	Annual Peport (Technical) of work done during the year 1940-'41 and Index for 1937-'41 by C. C. Inglis, A. R. Thomas, Rao Sahib D. V. Joglekar and staff at Khadakvasla.	7	8	0	1942	
IHR. 1,42	6	Annual Report (Technical) of work done during the year 1941-'42 by C. C. Inglis, J. S. Reid, Rao Bahadur D. V. Joglekar and staff at Khadakvasla.	7	8	0	1944	
IHR. 1.43	7	Annual Report (Technical) of work done during the year: 1942-'43 by C. C. Inglis, J. S. Reid, Rao Bahadur D. V. Joglekar and staff at Khadakvasla.	7	8	0	1945	
IWE, 1.43	8	Annual Report (Technical) of work done dur- ing the year 1943 by C. C. Inglis, Rao Bahadur D. V. Joglekar and staff at Kha- dakvasla.	7	8	0	1945	
IWE, 1.44	.9	Annual Report (Technical) of work done during the year 1944 and Index for 1940-'44 by Sir Claude Inglis, Rao Bahadur D. V. Joglekar and staff at Khadakvasla.	7	8	0	1945	
IWE, 1,45	10	Annual Report (Technical) of work done during year 1945 and Index for 1937 to 1945 by Rao Bahadur D. V. Joglekar and staff at Khadakvasla.		•••		In Press.	
IWE, 1.46	11	Annual Report (Technical) of work done during the year 1946 by K. K. Framji, Rao Bahadur D. V. Joglekar and staff at Khadakvasla.	7	8	•	1947	
		8 a g					

Page	Line	Incorrect	Correct
		. ,	
ii 3	21 from top. 20 from bottom.	Sanction Mr. J. J. Murray	Station Mr. J. B. Murray
23	Para 4, lines 1 & 2.	The width of the cill and sides is 3.5'	The width of the cill is 3.5
25	Para 7, line 7,	'C' by current mater	'C' by current meter
35	12 from bottom	Bisnasi	Birnasi
37	heading of column 2.	Total quantity of sand collected in all branches. Qs Qs	in all branches in Cft. Os in Cft. Os in Cft.
59	5 from top.	$R = \begin{bmatrix} \frac{Q}{f} \end{bmatrix}^{\frac{1}{3}} = \frac{Q^{\frac{1}{4}}}{m_{\frac{1}{6}}^{\frac{1}{4}}}$	Qs in Cft. R $\ll \left[\frac{Q}{f} \right]^{\frac{1}{3}} \ll \frac{Q_3^1}{m_6^{\frac{1}{3}}}$ 2. 48
61	3 from bottom.	assumed to be 0.7 mm.	assumed to be 0.17 mm.
61 70	2 from bottom. Para 3, 2.	$f = \sqrt{m} \times 1.76 = 73$.	$f = \sqrt{m} \times 1.76 = 0.73.$
77	line 8. Table IIA,	extent Bansbassa	depths extent Banbassa
77	Item 4. Table IIA, Item 6.	Yamuna dear	Yamuna near
77 81	Foot Note. Itom against	Prototope Prototope	Prototype
101	Page 12. 6 from bottom.	fact that	Prototype fact but
103	9 from bottom.	$h^{3}e \sqrt{\frac{H}{30}} = (\frac{3}{20})^{3} \times 40 \sqrt{\frac{3}{30}}$	$h^{3}e \sqrt{\frac{H}{30}} = \left(\frac{3}{25}\right)^{3} \times 40 \sqrt{\frac{3}{30}}$
103	3 below table 1.	V= 1.059 x 105	$V = 1.059 \times 10^{-5}$
117	23 from bottom.	thh	the
117 118	22 from bottom.	Strengte	strength
118	17 from top. 18 from bottom.	respec Barraage	respect Barrage
123	Para 6. 4. 2. line 8.	GOCAVE .	concave
135 135	5 from top. 8 from bottom.	nogue oross	vogue cross
145	column 11,	14,0000	14,000
154	Para 4 (a), line 1.	acon	soon
155	Para 4. 3, line 14.	opproved	approved
156 156	Para 4, 4(b), line 7. Line 5 from	A A CONTROL NO. 1	conditions
156	bottom. Line 4 from		the
166	bottom. 3, 2 line 5.	0.056	rather $0.056 \equiv 2.02 \text{ ft.}$
173 180	9 from top. Para 2, 2,	fouling 60,0000 cusecs	falling 60,000 cusecs
189	line 2. Line 2 from bottom,	E .	A four feet wide foot-bridge
204	14 from top.	envolved	
205	8 from top.	briged	evolved bridge
214	Para 4. 3,		TARABLE D

CONTENTS

T in the disc	Page
Introduction. 1. Introductory I the Government New Delhi.	Note by Mr. A. N. Khosla, Consulting Engineer to nent of India for Waterways, Irrigation and Navigation,
2. STAFF AND TH	SIR ACTIVITIES
2, 0	A. HYDROLOGY.
1. Rainfe	all and Run-off.
(i) Total	volume of run-off including the Standardisation of hydro-
A-1 (i)-1 Some Indus	features of precipitational variations in the Upper Catchment—a probability method of approach 6
	imum run-off discharge.
* * * * * * * * * * * * * * * * * * *	imum run-off formulae and their applications 19,
3. Meast	trement of flowing water.
A-3-1 Coefficie	nt of discharge in Notch type and Weir type Falls on anadi Main Canal (C. P.) 23
	B — THEORY OF FLOW AND DESIGN OF CHANNELS.
1 Flow i	n rivers and Canals.
(ii) Flou	in channels in incoherent and coherent alluvium.
	mparative analysis of sand by Puri sand meter and Air and meter 26
	C-HYDRAULIC WORKS.
1. Limit proto	tation of model experiments and comparison of model and types.
	ing the right bank of the Luni River at Balotra by of a repelling spur 34
	below the Central Sluices of the Mahanadi Anicut at-
2. Rive	r control.
(i) Flo	od Protection Work.
	distribution of sand load between the Mahanadi and atjuri systems at Cuttack—Orissa 35
(ii) Riv	er Training Work.
	rotecting the Right bank of the Kuakhai River above e B. N. Railway Bridge, near Cuttack—Orissa 39
	otection of the left bank of the Katjuri River at Khan-
C-2 (ii)-3 T	raining of the Ganga River at Kanpur 46
	shipra River at Ujjain—Gwaliar State—Preliminary ote and design of Model Scales 47
C-2 (ii)-5 M	easures for arresting bank erosion near Bhadeli and hagda villages on Auranga River—Bombay 51
°C-2 (ii)-6 Pi	rotective measures for several railway bridges on Madras Bombay line of M. S. M. Railway, between miles 82
aı	ad 113 52

		Page -
	Training of the Tapti River at Surat—Bombay	54
	Scour and erosion.	
O-2 (iii)-1	Mid-season scouring operations of the Right Pocket of Sukkur Barrage—Sind	. 61.
C-2 (iii:)-2	Apron design for the South Guide Bank of the Alexandra Bridge on the Chenab (N.W. Railway)	65-
C-2 (iii)-3	Scour below weirs	67
(vi)	Tidal action including that in estuaries.	
Č-2 (vi)-1	Measures adopted to reduce turbulence in the Hooghly River downstream of the Knuckle at the Titaghar Jute	
a 0 / -: 3 0	Mill	83.
• • • •	Preliminary note on the Cochin Harbour Model	91
• •	Dams and Weirs.	,
	Designs.	
•	Proposed design of Lower Sind Barrage at Kotri for effective sand exclusion from Canals—Sind	116.
C-4 (ii)-2	Regulation of Kotri Barrage—"Still Pond" or "Semi- open flow"—and consequent height of Pocket gates	134
(6)	Spillways.	
	omatic Gates on Tansa Waste Weir (Bombay)—Experints with half size model	153
C-6-2 Volument	nte Siphon Spillways—preventing scour below volute siphon llways by fanning out jets with dispersers and ledges.	165-
(8)	Canal Falls.	
	sipation of energy below Flumed Vertical Falls and Non- ned S. W. Baffle Falls	167
(10)	Excluders and Ejectors.	
C-10-1 Co of the	mparative Sand exclusion at the nose and at the raised sill the Approach Channel under present conditions and with Outer Bank extended to position Q—Experiments in 30: 1/40 part—width, Sukkur Barrage Model	177
	fect of change in regulation operations of the Right Pocket	111
on	sand exclusion—Experiments in 1/80: 1/40 part-width. kkur Barrage Model	179
	Other Works.	•
	apply of sand-free water to Jamshedpur Pump House	187
	reprise to test the suitability of the position of the Lock	201
	oan proposed in the Sind Design	191
. •	G - GENERAL.	
	Projects existing and proposed.	100
1. 1	Sakri River Project—(Bihar)	199
at	Posal for a Road - cum-Rail Bridge over the river Ganga Patna or Mokameh	203
	us Water to Cutch State— A note on the possibility of inging	219
Index for 19	943-1947.	

Index of The Cetnral Waterways, Irrigation & Navigation Research Stn,.

Poona-1, Annual Report (Technical), for 1943-1947.

Note:- Questions dealt with by The Director, but not described in

Annual Reports are marked with an asterisk. *

A	Pages of Annual Report (Technical) for the year					
	1943	1944	1945	1946	1947.	
Abrasion—attrition—degradation of sand.	62				1	
Accretion in N. W., Rice and Dadu Canals at Sukkur.		6,99	-, .**	,	•••	
Accretion of the river bed at Sukkur Barrage—causes of—and how to reduce rate of rise—Part II.		•••	59–66	137	. •••.	
Afflux—due to the proposed extension of the outer bank of approach channel—Experiments to improve flow conditions in approach			•••	25	***	
channel upstream of Sukkur Barrage, Indus River.		,		, , ,		
Afflux—reduction of, at Luni River Railway Bridge No. 3, of the Samdari-Raniwara Branch of the Jodhpur Railway,	•••	7=-	***	53		
Afforestation — Chos Act passed by the Punjab Government of—	3	* 	***	•••	••• 17.	
Ahmedabad (Bombay) — Khari River at Rajpur near— How to prevent outflanking of Barrage on—	(ii) *		*** !	•••	:	
Alexandra Bridge over the Chenab River near Wazirabad—steps repuired to prevent damage to the	(i)*	3 * ,5		بية لأ	65	
Amingaon — Brahmaputra Bridge near— design of	(ii)*	•••	irar	i 	•••	
Analysis of Bilot creek and Paharpur canal data (Ex. Indus 35 miles d/s of Kalabagh, N. W. F. P.) on the Indus.	32	***		•••	***	
Analysis of changes in the ccurse of the River Indus downstream of Kalabagh, N. W. F. P.	8		•••	•••	•••	
Analysis of Inundation Canal data in Sind and its comparison with the data of perennial canals.	29, 32	***	•••	•••	•••	
Analysis—Technical — of available data re:the rise of water levels of the Indus in the past and to be anticipated in future.	15	6,99	•••	•••		
Apparatus for generating waves in a model.	66		•••	•••	,	
Approach Channel—Preventing slips of the right bank of Indus River below the nose of appro- ach Channel upstream of Sukkur Barrage.	•••	•••	•••	,17		
Approach Channel at Sukkur—Design of off— take at the entrance to the right pocket from the		•	96	•••	•••	
Apron—Design of to protect the truncated nose, with maximum depth of scour—Indus River above Sukkur Barrage.		•••	•••	24	•••	

A & B	Pages of Annual Report (Technical). for the year					
8	1943	1944	1945	1946	1947.	
Apron design for the South Guide Bank of the Alexandra Bridge on the Chenab River N. W. Railway.	***	•••	111	***	5	
Aqueduct No. 23 of the Nira Right Bank Canal—Fluming of		***	•••	122		
Assam Access Road-prevention of Scour in Garang River on—	٠	3*	***	, 	•••	
Assam, Neamati in-Prevention of erosion at-	***	3*	,			
Attracting groyne-Revetment acts as	•••	2, 104	***		***	
Attracting island—Bukkur island in the Indus acts as an—		97	* ***	•••		
Attracting Islands to reduce turbulence in the Hooghly River d/s of the Kunckle at Titaghar Jute Mill.	•••	***		•••	83-	
Attracting Spurs—the use of—for training a river upstream of a bridge or a Barrage.	47	97_	•••	•••	****	
Attrition of sand-minimum velocity required for	62	•••	•••	***	***	
Attrition—Rate of attrition of sand in channels.	•••	***		115	***	
Augmentation of Bombay Water Supply.		***	***	137	:	
Auranga River, Training the—to protect Bhadeli village, District Surat (Bombay).	*		•••	<u></u>	51	
Automatic feed for maintaining a constant water level.		65	***	***	***	
Automatic gates spillway for the Tansa Dam— Determination of the coefficient of discharge of the		•	29-36		. 153	
B						
Baffle Fall-Hurdling over-		30		`•••		
Baffle platforms below S. W. F. s —Design of —		38				
Baffles-to dissipate energy below S. W. F. s- Design of-	, 	. 39	•••	•••	•••	
Bagaha—Gandak River at—on the Oudh & Tir- hut Railway which has outflanked the bridge —how to divert the—to its original course through the bridge.	(iii)*	10	•••			
Bakshi Khal.		13		***	•••	
Balta Jheel, & Solani Khadir in U. P Director's visit to the-	(iii)*	***	•••	•••	***	
Balta Jheel, & Solani Khadir schemes in U.P. —Model experiments in connection with—		59		***	***	

B	Pages of Annual Report (1 for the year				Pages of Annual Report (Techn for the year				
e productive and the second	1943	1944	1945	1946	1947.				
aluchistan — Protection of retaining walls from scour by means of repelling spurs.	. •••		8	•••					
arrage — Effect of constructing a — across a river, on bed levels and water levels u/s & d/s, with particular reference to the Indus (sind).	18, 19	99	: 1*** ::: :::::	 ;	• •••• • • • •				
arrage — Lower Sind Barrage on Indus at Kotri—design so as to exclude sand from ent-	·	å ••• •••	7 	98	116				
ering the canals at	** * * * * * * * * * * * * * * * * * *		524	2.					
arrage—Design of Lower Sind Barrage on Indus at Kotri — Optimum shape of the nose of	***		. : w	110	1 4.				
central island at Kotri. arrage—Lloyd Barrage at sukkur on Indus—to	•••			126					
control sand entering the canals taking off the arrage — Lloyd Barrage at sukkur on Indus —	- 36	a terri		, , , , , , , , , , , , , , , , , , ,	61				
midseason scouring operations of the right pocket of		in the							
arrage — Scour below Kotri Barrage.	, ···	•••			72				
arrage—Scour round divide wall noses of Kotri Barrage.		•••	1		73				
arrage — proposed design of Lower Sind Barrage — Long pocket versus short pocket.	•		•••		120				
arrage proposed at Kotri — design of right and					125				
left pocket divide walls.	• • •			, ,					
arrage proposed at Kotri — Comparisons of velocities during scouring operations with different number of left pocket spans.		•••	•••		130				
arrage proposed at Kotri—"Still pond or semi open flow" regulation and consquent height					134				
of pocket gates.	1,								
B. and C. I. Railway bridge at Broach—scour caused by left bank groyne.	•••	77, 85	••• • •	•••	•••				
eas River — Control of — by attracting spurs.	(ii)*	•••	•••	,					
ed load formulae — Schoklitsch's and Meyer Peter's & their comparison with Station formulae.	49, 50	•••	***	, 'c'."	·,				
sed ripples and bed waves.	53				•••				
eki, Balkadoba and Manas Rivers — How to train and control the —	(ii)*	3,69	•••		•••				
cell-mouth entrance of flumes and falls— side contractions and humps—		29, 32		• • • • • • • • • • • • • • • • • • • •	arii				
chivpuri scheme recommended for the augmentation of Bombay Water Supply.:	***	74		n	•••				
ibar—Ejectors for canals taking off the Son at Dehri—Head available for working the —	43	•••	, ,,,,	•••	•••				

Pages of Annual Repo for the ye							
	1943	1944	1945	1946	1947.		
Bihar—Son anicut at Dehri—Present method of regulating the—	40	,			***		
Bihar-Son river at Dehri-sand drawn by the canals and Undersluices u/s of the ancut.	41	58			•••		
Bilot creek and Pharpur canal—Analysis of data.	32			***			
Bombay Presidency — Raising the waste weir at Lake Arthur Hill, Bhandardara, with High Coefficient weir.		•••	•••	27	•••		
Bombay (Ahmedabad) — Khari river at Raj- pur—how lo prevent out - flanking of Bar- rage on —	(ii)•	•••	•••	, ui	•••		
Bombay City Water supply—Augmentation of—	2°	6, 70	***	137	153		
Bombay foreshore — Prevention of erosion on — and reclamation of land bearing S. No. 71, part of Juhu and creek - land.	1 5.4	1*	•••.		***		
Bombay, Nira L. B. Canal — Jeur aqueduct on the — Discharge formulae for	(ii)•	•••	*	•••	٠,		
Brahmaputra bridge near Amingaon — design of	(ii)*	•••	•••				
Brahmaputra — whether river ghat on — likely to be eroded.	(ii)*				•;•		
Breaches in the Damodar Left Bank Embank- ment d/s of Burdwan (Bengal).	7	***	•••	•••	•••		
Breaches in the Damodar River — proposals to prevent a recurrence of damage resulting from breaches in the —	(i)*	***	****	902	***:		
Breaches in the marginal bunds of the Indus above Sukkur — Rohri - Quetta Railway Realignment of the — necessitated by the danger of —	(ii)*		•••	•••	••• • • •		
Breaches in River Bunds in Sind —Technical enquiry into the causes of and steps required to minimize the danger of recurrence.	10. 20	•		•••			
Bridges — Dissipation of energy below	•••			139	***		
Bridge depth of foundations for bridge piers.				14	***		
Bridgesmaximum depth of scour downstream of		•••		140	69		
Bridge— maximum depth of scour at the heads of guide-bank & shanks, at the proposed C. K. Railway Bridge over Ramaganga River.		•••	•••	13	1		
Bridge — waterway required for Jodhpur Rail— way Bridge over Sukri River.	r			37	***		
Bridge — waterway required for Jodhpur Rail way Bridge over Sagi River.	•••	•••	•••	. 37	. •••		

B&C	Pages of Annual Report (Technical) for the year						
	1943	1944	1945	1946	1947		
Bridge Alexandra on the N. W. Railway—Apron design for the south Guide Bank on the Chenab River—	•••	eja i		1 40	65		
Bridges—scour at Guide banks.	·		•••		70 :		
Bridge on Beas River near Beas Station on the N. W. Railway on Lahore-Ludhiana section.	•••	2*	•••	•••			
Bridges on Madras Bombay line of M. & S. M. Railway between miles 82 & 113—protective measures of		***	•••	5 d	52		
Bridge piers—scour round	***	,	•••	129	***		
Bridge over Ganga River at Patna or Mokameh Ghat—proposed for combined Road and Railway Bridge—			, , , 1 /		203		
Broach—Scour caused by left bank groyne of the B. B. and C. I Railway Bridge at—		77, 85	•••		, , , ,		
Bruckner curve for sunspot numbers.		***	86-87		ent;		
Brushwood groynes, effective in eliminating "bellies" and return flow with "jetting" prevented by lowering pavement.	**************************************	25	•••	•••	44 4		
Bukkur island in the Indus acts as an AT- TRACTING island.	•••	97	***	18' I	1)		
Bulk proportionality and height of hump— Relation between—	. •••	44		•••	: <u>L</u>		
Bunds—River bunds in Sind—causes of breaches in	***			129	••		
G	15	6 S 4			1, .		
Calibration of a flumed bridge near Pimpra on the Nira L. B. Canal in Bombay Province.	•••	* 4*	***		•••		
Canals at Sukkur—Right and Left Bank, dif- ference in the behaviour of—	21			•••			
Canals, eradication of weeds from—during closures.	·	•••		124	·••		
Canals—Rivers and canals—flow in channels in incoherent & coherent alluvium.	•••		•••	85			
Canals—Exclusion of sand from entering the canals at Lower Sind Barrage on Indus at Kotri.	• • •	•••	•••	98.	116		
Cannals—Remodelling of		1.000	,	123			
Canals in Sind—Design of—Part I—New- Canals and Part II—Inundation Canals.	21	•••	•••				
Causes of accretion of river bed at Sukkur Barrage and how to reduce rate of Rise, Part I.		. 99	•••	414	**************************************		

C	Pages of Annual Report (Techni for the year				inical)
	1943	1944	1945	1946	1947_
Causes of accretion of the river bed at Sukkur Barrage and how to reduce rate of rise—Part II.	***		59-66	***	•••
Causes leading to erosion of the left bank of the Rupnarain River u/s of the Kolaghat bridge on the B. N. Railway.	***	14	h15	***	* ***
Causes of floods in Sind.	12	•••	•••	***	***
Cawnpore Electric Supply Corporation—How to secure an adequate supply of water for the river-side power station of the—	,	3*	***	e-#	•••
Central island or spur for river training.	47	97	•••		
Central Provinces—form drag of cylinders in connection with bridge foundations for—	(iii)•	•	•••	, 	
Ceylon—advice regarding probable maximum run - off from catchments in—	•	2*			g core
Ceylon—advice regarding waterway of bridges in -		2*	~ ***	, 111	•••
Channels-alluvial-factors affecting flow in		•••	***	134	•••
Channels—Factors affecting shapes of	22		•••		
Channels—Factors affecting silting & scouring of			***	132	
Channels—Punjab and Sind data of—Analysis of—	21		•••		
Chashma on Indus—Cause of changes of course of the river and how to control	(ii)*		•••		•••
Chenab river near Wazirabad—Alexandra Bridge over the—steps required to prevent damage to the	(i)•	3 *, 5	•••	•••	65
CHOS Act passed by the Punjab Govt. for afforestation.	3	•••	•••	•	***
Cistern—Design of—below flumes.		36, 40		•	•••
Classification of ripples and waves.	54	,	***		
Closing of spills on right bank u/s of Hope Bridge led to heavy erosion of the Rander Road.	,	87	***	***	
Cochin Harbour Model—Preliminary note on			***	,	91
Cochin Harbour—formation of mud banks at. Extracts of Report of the Special Committee 1938		***	•••		92
Cochin Harbour-movement of mud banks at	•	***	•••		112
Cochin Harbour-Notes on Tides near	•••	• • •	***		115

Cochin Harbour—Preliminary Report on improvement of —by K. K. Framji & T. M. Oag (1947). Cochin Harbour Model—design of scales. Coefficient of discharge of Ganesh lyer's volute siphon—Factors affecting the—	1943	1944	1945	1946	1947.
rovement of —by K. K. Framji & T. M. Oag (1947). Cochin Harbour Model—design of scales. Coefficient of discharge of Ganesh Iyer's volute siphon—Factors affecting the—					102
Coefficient of discharge of Ganesh Iyer's volute siphon—Factors affecting the—	•••			•••	
siphon—Factors affecting the—	•••			•••	
	10 5.752	•••	la marian		1
Coefficient of discharge of Standing Wave Flume.			92		****
Coeffficient of discharge of Standing Wave Flumes.—Effect of piers on	22	•••	94	•••	•••
Coefficient of discharge of Nira L. B. Canal Head Regulator.	·:**.	, .	95	*	••••
Coefficient of discharge of Notch type and weir type falls on the Mahanadi Main Canal (C.P.)			•••		23
Coefficient of discharge of the automatic gates spillway for the Tansa Dam—Determination of the—		••••	29-36		
Collapse of Rohri-Multan Road Bridge over Rohri canal at R. D. 52,000 in Sind—Pre- vention of—	75 ···	3*	15 22 ***	•••	***
Committee—Bombay Water Supply augmentation	(ii)*	•••		•••	
Committee Damodar—Technical and Joint committees by Government of India and Flood Enquiry Committee by Government of Bengal	1 & 2 *		•••	•••	•••
Committee—Delhi Water Supply—appointed by the Government of India.	1 *	•••	•••		
Comparison of sites for the Lower Sind Barrage.	***	55			i)
Comparison of Various Schemes for the augmentation of Bombay Water Supply.	(*****	71			
Construction of a 500 cs. Standing Wave-flume in Jodhpur State.	,	2*	1-1	•••	•••
Control blocks&deflectors in flumes—Design of—		36	•••	***	144
Control deterioration of the Mahanadi group of rivers at Cuttack (Orissa)—How to	(iii)•		494		
Control, how to and train the Beki, Balkadoba and Manas Rivers on B & A Railway (Assam).	(ii) *	3,69	•••	*	ž 1.
Controlling sand entering canals—Design of Lower Sind Barrage at Hajipur—	•••	57	:	•••	•••
Control of Beas river by attracting spurs.	(ii) •		:: :::::::::::::::::::::::::::::::::::		
Control of erosion due to littoral drift.	(ii) •	٠			
Control of erosion of Kshipra river at Ujjain.	(ii) •	2 *, 6	***		***
Control of flow through bridges by means of islands and groynes.	(iii)*	•••	***	***	***

O & D	Pages of Annual Report (Technical) for the year					
	1943	1944	1945	1946	1947.	
Control of Sand entering the canals taking off the Lloyd Barrage at Sukkur.				126	•••	
Control of the Jumna River at Tajewala by means of spurs.	(ii)•				•••	
Control of sand entering the Mithrao & Khipro Canals—Ex-Nara River at Makhi, Sind.	• •••	•••		127		
Controlling the sand entering the canals—off Son Aniout at Dehri (Bibar).	41	58	•••			
Crump's original design of S. W. F.	***	29			•••	
Culverts—road. Design of vent approaches & exits.			•••,	37	•••	
Curvature of flow—in a parallel sided 5' wide S. W. F. under various stages of flow.	***	. 		88		
Curvature of flow—in rivers and canals for controlling sand entering canals and training of tidal and non-tidal waters.	***	•••		125	•••	
Cut-off channel—new—factors favourable for opening a— (1) curvature of flow u/s; (ii) relative slope d/s of the bifurcation; and (iii) relative discharges.	•••	69	•••		* ****	
Curvature of flow.			19,43,	5, 17, 38, 42,44,52, 60,64,68, 98	34, 35, 39, 43, 46, 47, 54, 65, 83, 116,134,177 179, 187	
Cutch State — possibility of bringing Indus water to	•••	***		•••	219	
Cuttack, Orissa — Katjuri and Mahanadi group of rivers near—Experiments with a model of the—	37		19	44	35	
Cuttack (Orissa)— Kendrapara canal taking off Birupa River u/s of Mahanadi Aniout at — how to prevent silting of—	(iii) *			•••	•••	
Cuttack (Orissa)—Mahanadi & Katjuri—Dis- tribution of flood waters between—	37				• ••• •	
Cuttack (Orissa)—Naraj weir at—standing wave and drowned condition of the and their effect on the sand drawn by the Katjuri.	38	•••				
D ,	1					
Damage in 1944 to the Surat Rander Road and the City wall of Surat d/s of the Hope -Bridge at Surat and recommendations to ameliorate present conditions.	•••	87			•••	
Damage to lands bordering on the Tapti. Narbada and Sabarmati rivers during 1944 flood season.		84	•••		•••	

D.	Pages of Annual Report (Technica for the year				
	1943	1944	1945	1946	1947.
Damodar River Flood Enquiry Committee (Proposals to prevent a recurrence of damage resulting from breaches)—by Govern- ment of Bengal and Technical and Joint Committee appointed by the Government of India.	(i), 1, 2, 7*	5, 6, 13			
Damodar left bank embankment d/s of Burdwan (Bengal)—Breaches in the—	5		•••	***	· . ••••.
Damodar River, Bengal—proposals to prevent a recurrence of damage resulting from brea- ches in the—	***	3*))	
Damodar River—Transmission coefficient of the sand samples from the bed of, at Sindri.	***		***	94	•••
Damodar River-Floods & their control.	•••		204	133	
Danger of water - logging in the Eastern Nara Tract in Khairpur State in Sind. Darkeswar river.		3*	••4	•••	•••
Dates of beginning of depletion from Lake Tansa, Bombay—years 1896 to 1944.		73		•••	
Dates of break of monsoon at Tansa Lake (Bombay)—years 1896 to 1944.	· •••	73	***		. ••.
Datum area 1,000 ft. d/s of Sukkur Barrage before Right Bank approach channel was con- structed and after.		102	•••	·,	
Deep scour d/s of the N. W. Railway Bridge over the N. W. Canal near Ruk, Sind—Experiments carried out to evolve a suitable design of pavement and side expansion to induce accretion.	•••	23	20 D	•••	
Deflecting groyne—Measures taken to control erosion of the left bank of the Rupnarain u/s of the B. N. Railway Bridge at Kolaghat by means of a—			5–7	•••	·
Deflector for protecting the bed of the pavement of S. W. F. s and Baffle Falls—Design of—	. 40	*	***	411	***
Dehri-Groyne with a regulator to reduce sand entry from M. W. Canal at-		58	•••	. ir	•••
Dehri on the Son (Bihar)—Prevention of scour d/s of sluices.		20	•••		
Dehri on Son (Bihar)—sand excluding heads for the M. E. Canal & M. W. Canal on the—	40	58	- **	•••	•••
Dehri Son (Bihar)-Coefficient of discharge of weir.	•••	58	***	***	•••
Delhi Gate Pumping Station—Training of Jumna River at, with pitched embankment on the right bank.		***	43-48	•••	

D	Pages	t (Tech:	nical)		
	1943	1944	1945	1946	1947.
Delhi-Training of the Jumna at Delhi Gate Pumping Station,	1°. (iii)°	8	•••		
Delhi Water Supply Committee appointed by the Government of India.	. 1*	5	***	(*4 1)	***
Denudation, erosion & floods.	3	***	***	146	
Denudation—soil—excess sand charge due to—	5	100		***	
Depth of scour — maximum, for apron protec- tion at the truncated nose of extended outer bank of approach channel in the Indus above Sukkur Barrage.	•••	•••	***	24	•••
Depth of scour—maximum, at the heads of guide banks—Ramganga River at proposed C. K. Railway Bridge.	***	•••	***	13	• •••
Depth of scour — maximum at the shanks of proposed C. K. Railway Bridge over Ramganga River.		415	1119	13	•••
Depth of scour — maximum at Bridge section Ramganga River — at proposed C. K. Railway Bridge.	***	(***)	(***)	14	
Depth of foundation for Bridge piers at the proposed C. K. Railway Bridge over Ramganga River.	***		***	14	400
Design of a stilling basin d/s of the overflow section of the main Erinpura Dam in Jodhpur State.		2*	: 431	411	******
Design of approach channel of Flumes and Falls.	,	31	•••	***	gene.
Design of canals, in Sind, Part I—New canals and Part II — Inundation canals.	21		•••	136	•••
Design of channels u/s of S. W. F. s.	•••	31	,		•••
Design of canals — comparative analysis of sand by Puri sand-meter and Air sand-meter.	***		•••	***	26
Design of cistern below flumes.		36, 40	·	***	1***
Design of downstream portion of S. W. Flumes, standard design—where very high recovery of head is not essential.		35	***	•••	•••
Design of downstream portions of S. W. Flumes, standard design—where it is important to lose as little head as possible.	***	37	•••		•••
Design of guide banks and divide walls down- stream of the new undersluices of the Son at Dehri (Bihar).	(22	•••	***	. ***
Design of the Lower Sind Barrage—Experiments to test the design for scour and sand exclusion from canals — Sind.	8**	,44	48-59	127	116,134
Design of Lower Sind Barrage at Hajipur.	4, 6, 55	***		***	***

D	Pages	rt (Tech ar	nical)		
	1943	1944	1945	1946	1947.
Design of new canals in Sind—recommendations for bed width, depth, slope.	27	2*	•••	***	•••
Design of off-take at the entrance to the right pocket from the approach channel at Sukkur.			96		•••
Desilting and dredging of Tanks in Sangli State.	·	2*	•••	***	
Determination of the coefficient of discharge of the automatic gates spillway for the Tansa Dam.		•••	29-36	•	•••
Determination of the variable coefficient of the 10,595 cs. Tando Mastikhan Fall on the Rohri Canal, Sind.		***	94		•••
Device to ensure stilling before water is let into a model.	el ² 0 444	105		***	
Dickens' run-off formula.	67	***	***		
Difficulties experienced in river model experiments due to effects caused by vertical exaggeration.	•••			110- 115	
Discharge — Accuracy of different methods of taking discharges.	***			86	•••
Discharge measurement — coefficient of discharge in Notch type and weir type falls on the Mahanadi Main Canal (C. P.)			2	***	23
Discharge Table of S. W. Flumes and Falls.		34			
Dispersers — to prevent scour below volute Siphons by fanning out the siphon jets.		•••	•••	•••	165
Disposal of Poona Sewage by irrigation.			400	123	
Dissipation of energy below falls.		29		139	167
Dissipation of energy d/s of Lower Sind Barrage (2400 ft. u/s of site B near Hajipur)—Experiments in connection with —	***		9-11	•••	308 -
Dissipation of energy of flow of the jets issuing from "Gan-sh Iyer" Volute siphon by mutual impact of jets.	• •••	****	•••	91	***-
Divergence from regime in stable channels in	8 2	* 5			-
alluvium—Note on, by the Director.	,	***	***	135	•••
Dock — How to reduce waves in a, caused by swell in a harbour.	66	•••	g ••••	***	444,
Downstream expansions — Rectangular Hyperbolic U. P. design adopted in flumes and falls.		35, 37, 40			a 110
Drainage channels of the Damodar River.		13		•••	
Dunbar Cotton Mill — Training the Hooghly River at — with a bypass channel.			11-18	s-200	100

D&E.		Pages of Annual Report (Technical) for the year				
	1943	1944	1945	1946	1947,	
Dunbar Mill—Longitudinal and cross row of piles at the—to enable accretion and silting to take place.		7	*14	;···	•••	
Dunbar Mill on the hooghly — Erosion of bank near the, how to prevent, by a tidal model.	•••	7	8 - III	•	•••	
E				ì		
Eastern and Western Jumna Canals — Headworks at Tajewala.	• •••	91	•••	5	***	
Eastern Nara & Rohri Canals (Sind)—Fluctua- tions of grade of materials exposed on the beds of—	. 35		310 4	`	•••	
Effect of constructing a barrage across a river on bed levels and water levels u/s and d/s with particular reference to the Indus (Sind).	17	.99	•••			
Effect of closing the Head Regulator of the Robri Canal (Sind) from the top downwards, on the canal regimen.	35	•••	-	•••		
Effect of constructing a trench d/s of a soil dam on the saturation line.		61	***	***	•••	
Effect of high level bridge pavement on scour .d/s of the Railway bridge on the N. W. canal at Ruk, Sind.		23	400	:•••	• •••	
Effect of shape of catchment on the run-off.	140	68			***	
Effect of staunching due to silting upstream of the Solani dam.		63	***	***	•••	
Effect of storages in Tons and Giri catch- ments on supplies in the Jumna during flood season and regeneration in the fair season.	••• 8	94	***	***	•••	
Effect of variation of u/s and d/s water levels of the Solani Khadir dam model on Hydraulic gradients or saturation lines.	•••	61		, 	:	
Effect of shortening Barrage on accretion in the Indus d/s of sukkur Barrage.	***	3	· ··	***	•••	
Effect of size distribution of particles, specific gravity, charge of bed sand and discharge, on ripples.	56	•••	(***	***	•••	
Effluent Experimental Farm — disposal of Poons sewage by irrigation.	9 ₹ •••	***	***	123	***	
Ejectors for cauals taking off the Son at Dehri (Bibar). Head available for working the—	43		•••	***	•••	
Elutriator—sand and silt—grading sand and silt by washing.	64	···	•••	***	***	
Embankment near Nanpara (U. P.) to divert the whole of the Saraju river into the Gograi, thus preventing spill flowing into the Saraju Tirhi channels.		2*	•••	••• 4	•••	

E	Pages of Annual Report (for the year				nical)
	1943	1944	1945	1946	1947.
Embankment—pitched, to attract flow at the Delhi Gate Pump House on the Jumna River.		•••		60	•••
Emergent measures for preventing serious damage to the central sluices of the Mahanadi Anicut at Cuttack—Orissa.		•••	•••	27	34
Emperical run-off formulae.	67	*			•••
Energy dissipation below Standing Wave Flume Falls.	- N.	29	•••	•••	•••
Energy—dissipation of energy of jets issuing from Ganesh Iyer Volute Siphon by mutual impact of jets.	."	···	•••	91	
Engineering Congress (Punjab) Paper 275 (1945) "River Training and Control by Pitched ('Attracting') islands".		97			1
Equivalent size and specific gravity of stones and blocks in a model.			115- 116		. ••
Eradication of water weeds from Canals.				124	***
Erinpura Irrigation and Hydro-electric Project Siphon spillways in Jodhpur State.		2*	•••	4	·:
Erosion—bank, on Auranga at Bhadeli & Bhagda villages (Bombay Presidency)—Measures arresting the	***		***.	1.54	51
Erosion at Neamati in Assam—Prevention of—		3*		***	••• •••
Erosion at Ratnagiri—How to improve conditions and prevent further—	(ii)*	•••	•••		·
Erosion at Vizagapatam foreshore—prevention of—	1	3*	•••	1.	•
Erosion-control of-due to littoral drift.	(ii)*			***	***
Erosion, denudation & floods.	3	•••	***	***	
Erosion just u/s of the B. N.Rly. Bridge over the Rupnarain River—How to check dangerous—	(iii)*	2°,	•••	***	444
Erosion of Spur 2 in the Indus River near Umerkhel—action to be taken regarding	,,,,	3*	•••		
Erosion of the right bank of the Indus above Rohri and danger of breach of the main line, N. W. Railway.	(ii)*	•••	•••	•••	. ***
Erosion—Prevention of—on Bombay Foreshore and reclamation of land bearing S. No. 71, part of Juhu and creek-land.	•••	1	•••	•••	
Estimated depth of scour at bends.		75	***	••••	
Estimation of the maximum flood discharge during 1944 by various methods and comparison with the fan catchment formulae.		89	***		•••

E&F	Pages of Annual Report (Techi for the year				nical)
	1943	1944	1945	1946	1947.
Excluders and Ejectors—Effective exclusion of sand from canals at the proposed Lower Sind Barrage on Indus River at Kotri.	•••	***	•••	98	
Exclusion of sand from entering canals by construction of submerged vane at the proposed Lower Sind Barrage on Indus River at Kotri.	•	. 908	164	101	. •••
Exclusion of sand by Central Island at the pro- posed Lower Sind Barrage on the Indus at Kotri.	····		•••• •	105	•••
Exclusion of sand—factors affecting the exclusion at the proposed Lower Sind Barrage on Indus at Kotri,	***	•••	•••	105	•••
Exclusion of sand from canals taking off the Son river in Bihar,	•••	58	•••		1100
Experiments in connection with dissipation of energy downstream of Lower Sind Barrage (2400 ft. upstream of site B near Hajipur).		•••	, 9-11	***	
Experiments to determine a suitable profile of the Lower Sind Barrage to cause minimum afflux with gates fully open.	***		22-29	•••	•••
Experiments with a vertically exaggerated model (1/400: 1/66) of the Mahanadi and its branches at Cuttack (Orissa).	***	***	19-22		•••
F			3		
actors affecting deltaic rivers.	8		700		
actors affecting meander of channels.	51	•••	•••	•••	 •••
Factors affecting the coefficient of discharge of Ganesh Iyer's volute siphon.	,*	•••	72-78	. •••	
Factors affecting the shape and dimensions of ripples & waves.	. 56			***	
Factors affecting slope in alluvial channels.	***	***		134	
Factors favourable for opening a new cut-	9	1 1	2000	æ •	
 (i) Curvature of flow u/s. (ii) Relative slope d/s of the bifurcation. (iii) Relative discharges. 		69	***	***	•••
Fair weather and freshet spring tides in the Rupnarain River at Kolaghat Rly. Bridge on the B. N. Railway in 1944 and in its mobile bed model.	•••	17	•••	•••	•••
Falling aprons—characteristics of				129	
Falls on Mahanadi Main Cannal (C. P.)—co- efficient of discharge of Notch Type and Weir Type Falls—		.,.		••••	23
Falls—dissipation of energy below		•••		139	167

J.F	Pages of Annual Report (Technical) for the year					
	1943	1944	1945	1946	1947.	
Falls, Flumed—scour d/s of	w.	٠	, 93	٠		
Field results of measures adopted after model experiments.			•••	5		
Flood control.				131	2	
Flood control—Floods in Damodar River.	•••		•••	133	•	
Flood control on Tapti River at Surat,	•••		•••	· · · · · · · ·	54	
Flood discharge—maximum, of Ramganga River for proposed C. K. Railway.	***	1	•••	13		
Flood protection measures for Nuna-Pothi Rivers in Orissa.	*** _H . M . 1	3*	***		•••	
Flood protection—Redistribution of sand load between the Mahanadl and Katjuri systems	•••	•••	19	44	35	
at Cuttack—Orissa.						
Floods—causes of—in Sind.	12	•••	•••	•••	•••	
Floods, denudation and erosion.	3		***	1 - Energy of 107	,	
Floods, river—Sunspot intensity cycles as a medium of predicting the probable dates of occurrence of—	•••	. •••	86-87	•••	•••	
Fluctuations of grade of materials exposed on the beds of the Eastern Nara and Rohri Canals (Sind).	35		•	•••	***	
Flumes—Dissipation of energy below	97.8			139		
Flume Meter Baffle Falls—Design of down- stream portion of—		35	•••			
Flumes—pebble—bed-Transportation of pebbles in—	47				•••	
Flume—Standing Wave Flume Design for the Jawai River Project (Jodhpur).		***		86	, •••,	
Flume—Water Surface profile in a 5 ft. wide S. W. F. with parallel sides, at various stages	. 2". 3 0	•••	•••	86	••••	
of flow.					i,ā	
Fluming of Aqueduct 23 of the Nira Right Bank Canal.	•••	***	•••	122	***	
Flumed Falls—Scour downstream of—		144	97	314		
Form drag of cylinders in connection with bridge investigation for Central Provinces.	(iii) *	4*	•••			
Forty cusecs Standing Wave Flume in the masonry conduit, taking off from the Haleji Reservoir—Karachi Water Supply scheme.		2*	•••		•••	
Freshet spring and fair weather tide in the Rupuarian River at Kolaghat Railway Bridge on the B. N. Railway in 1944 and in its mobile bed model.		17	•••	•		

C	Pages of Annual Report (Techni for the year				nical)
	1943	1944	1943	1946	1947.
Gandak River at Begaha on the Oudh and Tir- hut Railway which has outflanked the Bridge—How to divert the—to its original course through the Bridge.	(iii)* 	3, 10, 13			eet
Gandak at Bagaha on the Oudh and Tirhut Railwayconditions leading to the outflanking of the Railway Bridge.	***	10	***	341	* 200
-DoDo- Chhitauni groyne acting as an 'attracting' spur in pulling the river round its nose.) 20 pro- 20	10		- 114	***
-Do -Do- Prediction of the future movement of	***	- 13	•••	***	•••
-Do- sand on the bed of the	56 N	11	***	,,,	414
-DoDo- use of the Missi- sippi formula for estimating the maximum flood discharge in the—in 1924.	•	12	***	pserings ▼ ■ ■ iii	• •••
Ganesh Lyer's volute siphon—Factors effecting the coefficient of discharge of—	•••	•••	72-78	•••	•••
Ganga River—Safeguarding the Harding Bridge across—against the danger of outflanking.	;••	***	•••	128	***
Ganga—Maximum scour profile between guide banks of the—at the Harding Bridge.	4	***	•••	(199)	***
Ganga River—Proposal for a combined Bridge at Patna or Mokameh Ghat over the	•••	•••	•••	•••	203
Ganga River-Training the river at Kanpur.		***	***		46
Garang River on Assam access Road—Prevention of Scour in—	***	3*	***	•••	***
Geometrically-similar models which give geometrically-similar results.	•••		92-95	•••	***
Geometrically-similar models which do not give geometrically-similar results.	***	***	95-101	•••	.: : ## ₽:
Gibb modeles—Theory, design & construction of—		,'		122	***
Giri and Tons catchments—effect of storages in—on supplies in the Jumna during flood season & regeneration in the fair Beason.	100	94	44.6	#**	* •
Glacis slope downstream of S. W. Flumes.	•••	35	***		***
Glacis slopes of Flume Falls.		38	***	•••	***
Godavari Right & Left Bank canal Head Regulators (Bombay Presidency)—Experiments with	•••	***	***	122	•••
Grading sand and silt by washing.	64		***	*13	***
Groyne, deflecting—Measures taken to control erosion of the left bank of the Rupnarain upstream of the Bengal Nagpur Railway Bridge at Kolaghat by means of a—	***	***	5-7	bef	900

G&H	Pages of Annual Report (Technical) for the year					
	1943	1944	1945	1946	1947	
Groyne repelling—Proposal for protecting the left bank of the Rupnarain River u/s of the Railway Bridge at Kolaghat on the B. N. Railway.	•••	. 15	•••	*** ⊕	***	
Groynes & islands—control of flow, through bridges by means of	(iii)*	97	•••	•••	•••	
Groynes, attracting and repelling.	47	104	***	***	110	
Groynes, Brushwood, effective in eliminating 'bellies' and return flow due to 'jetting', prevented by lowering pavement.	•••	25	• ••	. (44)	•••	
Groynes—Semi-permeable—construction and launching of	•••		***	66	. •••	
Groynes—Timber pile groynes.	•••			67		
Groynes—to train the Sutlej River at Samasata Railway Station, N. W. Railway.		•••		72	•••	
Groynes—permeable tree groynes to reduce attack on right bank upstream of B. N. Railway Bridge at Kolaghat.	•••	•••	•••	78	•••	
Groynes—permeable tree groynes to train the Indus river at mile 21 of the Sukkur Begari Bund—Sind.	•••	• •••		81		
Groynes—maximum depth of scour at the head of		gen	***	140	•••	
Groynes—for silting a bye-river at its off- take—Indus River opposite mile 5/3 of Kasimpur Nababshah Bund.	3.44	•••		83	•••	
Guide Bank—Maximum depth of scour at the heads of	•••	•••	·	140	*	
Guide Bank—design of the left guide bank of the Luni River Bridge on the Samdari-Rani- wara branch of the Jo dhpur Railway.			*	59	' ***	
Guide Bank—Maximum scour at Ramganga River—proposed bridge on C. K. Railway.		•••	•••	13	***	
Guide Bank—Length of, necessary measures to prevent probable erosion of Railway Embankments.	140	•••	07:1 81 191 • 1 •1	15	•••	
Guide Bank design of—at the proposed Lower Sind Barrage at Kotri—Sind.			, ••••	•••	122	
Guntakal-Beswada section of the M. & S. M. Rly.—Heavy run-off from a small catchment us of a bridge on the—which caused the river to overflow the embankment and Railway track causing an accident.	44	•••		: 6	***	
H ·		E		N N	Ĭ.	
Hajipur, Sind, Design of Lower Sind Barrage at		55			25	

н		Pages of Annual Report (Technical) for the year				
	1943	 1944	1945	1946	1947.	
Haleji Reservoir — Karachi water Supply Scheme—Forty cusecs S. W. F. in the masonry conduit taking off from the	, 	2*	•••	•11		
Harbour—How to reduce waves in a dock caused by swell.	66	•••	•••	•••		
Harbour—Preliminary note on model of Cochin—		•••	,	***	91	
Hardinge Bridge—over the Ganges (Bengal Assam Railway); protection against the danger of being outflanked.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	•••		128		
Head Regulator—Godavari Right Bank Canal and Left Bank Canal—Increasing the capa- city of	••••	••• • a	***	122	•••	
Head Regulator—Nira Left Bank Canal—In- creasing the discharging capacity of	3	•••		. 122	•••	
Headwork-Punjab practice of constructing		. 98				
Heavy run-off from a small catchment u/s of a bridge on the Guntakal Bezwada section of the M, & S. M. Rly. which caused the river to overflow the embankment and railway track causing an accident.	44			•••	•••	
High Coefficient Weirs.		***	99-101	141		
High level stone pitching maintained at Hope Bridge near Surat distorted curvature of flow & caused damage upstream and downstream in 1944.	•••	88		•••	•••	
Historical review of steps taken by the Sind Government to collect data in connection with the Indus and to control it in its passage through Sind.	11	***	•••		•••	
Historical Account of the Indian Waterways Experiment Station, Poona (1916-46).				-121	•••	
History of the water supply of Bombay.		70	***	•••		
Hooghly River above Calcutta—How to improve		3	••••	***	•••	
Hooghly river—Tidal model to prevent bank erosion near Dunbar and Titaghar mills.	35	3, 7	,	•••	•••	
Hooghly River—Measures adopted to reduce turbulence in the river downstream of the Knuckle at the Titaghar Jute Mill (Bengal).		•••	•••	. 38	83-	
Hooghly River—Experiments with submerged row of piles at the knuckle at the Titaghar Jute Mill (Bengal).		1.00	•••	39	•••	
Hooghly rigid tidal models.			105-107	•••	•••	
Hoogly River at Dunbar Cotton Mill—Training the—with a by-pass channel.	***	•••	13-18	•••	***	
	i i					

H&I	Pages of Annual Report (Tech for the year				
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	1943	1944	1945	1946	1947
Hooghly semi-rigid tidal model (long).	443	: `aaq •	105		,•••
Hooghly River—Experiments with "attracting" artificial Islands.	•••	•••	•••	40	•••
Hooghly River—protection of the foreshore of the Anglo-India Jute Mill on the	•••	•••	•••	42	•••
Hooghly River—Preventing erosion along the foreshore above Calcutta.	e	****	1 g 1 s; •••	130	::
Hooghly Semi-rigid tidal model (Short).			106	••• ,	8
Hope Bridge near Surat—closing of spills on right bank u/s of—led to heavy erosion of the Rander Road.	***	88	****	•••	'
Hur Hura khal.		13	ar iz	in	
Hurdling over Baffle wall.		30	!	•••	***
Hydraulic elements and constants—Nomograms for determining the			78–80		
Hydraulic gradient or saturation lines—effect of u/s and d/s Water levels of the Solani Khadir dam model on—		61	1 / 12. 		
I	* .			i.	5 .1
Improvement of the Rice Canal due to the	33		; •••,	***	
Right Bank approach channel at Sukkur. Increasing the discharging capacity of Regulators,	,		70 (122	
Outlets & Aqueduots by fluming & remodelling.	•••				
Indian Waterways Experiment Station, Historical Account of—1916-1946.		•••	1 Su	121	•
Indus above Rohri-Erosion on the right bank of the and danger of breach of the main	(ii)*		•••	•••	***
line N. W. Railway.					
Indus River, training of—Above Sukkur Barrage to prevent slips of the right bank below the nose of the Approach channel.	<u>}***</u>	•••		17	•••
Indus above Sukkur (Sind)—Realignment of the Rohri-Quetta Rly. necessitated by the danger of breaches in the marginal bunds of the—	(ii)*	•••	•••		•••
Indus—Analysis of Bilot creek and Paharpur Canal data (Ex Indus) 35 miles d/s of Kalabagh, N. W. F. P. in—	32	• • •			•••
Indus and the Liyod Barrage at Sukkur—Experiments with a model of the, for sand control of the right bank canals.		•••	*. :: :	26	61, 177 179
Indus, Sukkur-accretion in-		6, 99	1 /2 2 mag	1c.;	
Indus, Bukkur island, in the-acts as an attracting island.		97			

	Pages of Annual Report (Tec for the year				nical)
	1943	1944	1945	1946	1947
Indus at Sukkur (Sind)—New factors which will affect rate of rise of water levels in the—	. 17	•••	***	•••	•••
Indus—downstream of Kalabagh—analysis of changes in the course of the—	7	•••	638		•••
Indus—Jamshoro bund on the left bank of the—near Hydrabad (Sind).	39	•	***	***	4++
Indus River—Experiments to improve conditions in the Approach Channel.	•••	٠	***	19	•••
Indus River—Stability of the proposed trunca- ted nose for a super-flood of 9,00,000 cusecs in the 1/80 G. S. Model.	,,,	•••	***	22	***
Indus River—Maximum depth of soour for apron protection at truncated nose of Approach Channel.	•••	•••	•••	24	•••
Indus River—Afflux due to the proposed extension of the outer bank of Approach Channel.		***	. ***	25	•••
Indus River—Training of the River at mile 21 of Sukkur Begari Bund by means of permeable tree groynes.	***		- ***	81	
Indus River—Design of Lower Sind Barrage at Kotri, so as to exclude sand from entering canals.	•••	•••	***	98, 127	
Indus River—Experiments with model, with & without proposed Lower Sind Barrage at Kotri.	•••		•••	99	***
Indus River—Factors affecting the exclusion of sand from the canals, at the proposed Lower Sind Baraage at Kotri.	•••		***	105	***
Indus River—Scale ratios of the Lower Sind Barrage model at Kotri.	•••	·	. ***	107	•••
Indus near Umerkhel—action to be taken regarding erosion of spur 2 in the—	## ##■■	3*	***	•••	•••
Indus-rate of rise of water levels in the-	15	99	***		***
Indus near Cashma—Cause of change of course of—and how to control—	(ii)*				•••
Indus—Probable effect of constructing the Kalabagh Barrage on the course of the—	10		•••		•••
Indus— Protection of N. W. Railway embank- ment u/s of the Bukkur gorge.	13	•••	•••	•••	***
Indus (Sind)—Breaches in the-	20	•••	***		***
Indus (Sind)—effect of constructing a barrage across a river on bed levels and water levels u/s and d/s with particular reference to the—	18	99	•••	•••	***
Indus (Sind)—Specific discharge gauges at Bachalshah on the—	•••	101	•••		

INDEX		so.	5		241
I & J	Pages		ual Repo or the ye	rt (Tech	nical)~
v Bandizes v sab	1943	1944	1945	1946	1947.
Indus—Technical analysis of available data regarding the rise of the water levels of the—in the past and to be anticipated in future.	. 15	, , , ,	***	***	
Indus—Technical enquiry into the causes of breaches in the River Bunds in Sind and steps required to minimize the danger of recurrence.	1, 10	, m		•••	***
Information regarding rainfall, run-off Formulas and rate of silting of reservoirs required in connection with a scheme in Transval, South Africa.	•••	2*	•••	•••	
Inglis' fan catchment discharge formula, intro- duction of shape factor in—	67	•••	6 1 00 1 10 00 1	•••	***
Inundation Canals in Sind—Analysis of—and its comparison with the data of perennial canals.	29		••• •••	•••	
Inundation Canals in Sind—Design of—	29	344	ne State	1 . #44.	,,,,
Irrigation—Controlled, in the Bombay (Deccan).		•••	- 440	122	
Island at Suleimanki.	•••	99		***	
Island for the Lower Sind Barrage site C.	: 1,	98		•••	••••
Islands and attracting spurs—use of—for training a river.	47	97			
Islands and groynes—Control of flow through bridges by means of—	(ii) •	•"		•••	•••
Islands for holding a river.	47	***	•••	•••	
Islands u/s of the Barrage at Kalabagh.	1	'98		•	9.
Islands—Experiments with artificial "Attracting" islands to train the Hooghly River at Titaghar Jute Mill (Bengal).		111.0		40	83
Islands—Experiments with artificial "attract- ing" islands at Luni River Railway Bridge No. 3, of the Samdari Raniwara Branch of the Jodhpur Railway.		•••	***	53	
Islands—Effect of central island on exclusion of sand from canals, at the proposed Lower Sind Barrage on the Indus at Kotri.	•••	•••		105	Per
Island—Optimum shape of the nose of central Island at Kotri for the proposed Lower Sind Barrage on Indus.	1.05	***	• •••	110	•••
, , , , , , , , , , , , , , , , , , ,		n ai 215			69
Jamrao & Sukkur Barrage Canals - Relationship between surface width and Q of-	25		****		•••
Jamrao and Sukkur Barrage Canals—Relation- ship between S & Q.	26			***	•
Base a s	A . 1 %.	9.5	- B	7 L. J. 1	S 60

J	Pages		al Repor	t (Tech	nical)
	1943	1944	1945	1946	1947.
Jamrao Canals, Sukkur Barrage Canals, L. C. C., L. J. C. (Punjab)—Relationship between area and discharge of	23	***	***	,,,	***
Jamshoro Bund on the Left Bank of the Indus near Hyderabad (Sind).	- 39	•••	•••	***	***
Jawai River-Design of S. W. F. for (Jodhpur).	86	• •••	***	. ***	***
"Jetting" below Canal Falls & Bridges.	- m.	25, 30			PR C
"Jetting" prevented by Lowering pavement level at Railway Bridges.	***	, 25		•••	***
Jeur Aqueduct on the Nira L.B. Canal (Bombay)—Discharge formula for—	(ii)*	•••	•••	••••	4**
Jodhpur Railway line—Training of Luni River to prevent it damaging the—		•••	36-42	•••	
Jodhpur Railway—How to control Luni River where it is crossed by the Samdari-Raniwara Branch Line on—	101	3*		***	***
Jodhpur Railway—Steps necessary to protect main Line—from Hyderabad to Luni June- tion on—from damage by Luni River floods.	•••	3* 5	***	•••	
Jodhpur State—Design of a stilling basin d/s of the overflow section of the main Erinpura Dam in—	•••	2•		***	***
Jodhpur State—Construction of a 500 cusees Standing Wave Flume in—	**	.2*			>**
Jodhpur State—Erinpura Irrigation and Hydro- electrical Project siphon spillways in—	:•••	2*		•••	***
Jodhpur State—Runoff from Erinpura Reservoir.		68	,,,		•
Jumna at New Delhi—Present and future water requirements and supplies in the—	•••	91	•••	138	***
Jumna at New Delhi—Training of the, near Delhi Gate Pumping Station.	(iii)*	4, 8	194	60	***
Jumpa River at Delhi Gate Pumping Station— Training of—with pitched embankment on the right bank.	***	•••	43-48	•••	gaa
Jumna, River at Tajewala—Control of—by means of spurs.	(ii)°	•••	***		***
Jumna River—Relation between floods in the monsoon and regeneration in the hot weather in the—	•••	93		•••	•••
, K					¥
Kalabagh—Analysis of changes in the course of the River Indus downstream of—	8	•••		•••	114
Kalabagh Barrage—Islands u/s of the	***	98	•••	•••	

K	Pages	of Annu	al Repor		nical)
· ***	1943	1944	1945	1946	1947.
Kalabagh Barrage—Probable effect of construct ing the—on the course of the Indus.	9		•	•	,
Karachi water supply scheme—40 cusecs Standing Wave Flume in the masonry conduit taking off from the Haleji Reservoir.		2*	***	•••	•••
Katjuri and Mahanadi at Cuttack (Orissa)— Distribution of flood waters between—	· 37	•••	19	44	35
Katjuri—Standing wave and drowned conditions of the Naraj weir at Cuttack (Orissa) and their effect on the sand drawn by the—	39		, •••	•••	
Katjuri River—protection of the left bank of— at Khannagar upstream of the Railway Bridge—Orissa.	***		•••	•••	43
Kendrapara Canal taking off Birupa river u/s of Mahanadi aniout at Cuttack, Orissa—How to prevent silting of—	(iii)•	***			•••
Khairpur State (Sind)—Danger of waterlogging in the Eastern Nara tract in—	***	3*	•••	•••	• •••
Khari River—Minimum waterway required for Jodhpur Railway Bridge on	•••	•••	5	37	
Khari River at Rajpur, near Ahmedabad (Bombay)—How to prevent outflanking of Barrage on—	(ii)*	2*	•••	,	
			٠,	1	- · ·
Khipro Canal (Sind)—Remodelling the, for sand exclusion.	***	•	· · · .**	127	
Knuckle at Dunbar Cotton Mills—Longitudinal and cross row of piles at the—to enable accretion and silting to take place.	***	7, 8		·	***
Kosai River.	•	13	***		
Kosi gorge—Land slides in the	. 3				
Kosi River—Factors affecting rapid westerly movement of—	. 5	244	•••	132	•••
Kotri and Sukkur—Silt in suspension at—since 1913—Quality of—	19	***	•••		•••
Kotri Barrage—proposed design of, for effective sand exclusion from canals—Sind.	•••	•••	21 444 0		116
Kotri Barrage—Regulation of—"Still pond" or "Semi open flow"—and consequent height of pocket gates at		,	•••		134
Kshipra River at Ujjain-Erosion of-control of	(ii) •	2 , 5			47
Kuakhai River—protecting the right bank of, above the B. N. Railway Bridge near Cuttack (Orissa).	•••	*** ***			39
Kuakhai River—design of guide bank, above the B. N. Railway Bridge at Cuttack.	;***	***			41

L	Pages of Annual Report (Technifor the Year				nical)
	1943	1944	1945	1946	1947.
Land Drainage-In the Bombay Deccan.	***	RAD		121	
Landslides in the Kosi gorge.	3		•••		
Leakage through Solani embankment.	121	63			7
Littoral drift-control of erosion due to-	(ii)*	***	***	•••	
Lloyd Barrage—Soil survey of area commanded by	***		•••	123	***
Lloyd Barrage—Training of the Indus River above Sukkur Barrage to prevent slips of the right bank below the nose of the Approach Channel.	***	***	•	17	•••
Lloyd Barrage—Stability of the proposed truncated nose for a super-flood of 9,00,000 cusecs, in the 1/80 G. S. model.	***	•••	•••	22	111
Lloyd Barrage—Afflux due to the proposed extension of the outer bank of Approach Channel at	**** ****		***	25	***
Lock Span—proposed design of—in Lower Sind Barrage at Kotri.	•••	•••	•••	.,.	191
Low level Weir downstream of Delhi Gate Pumping Station—effect of constructing a—on the low water channel at the Pumping Station.	***	8, 9	bet	•••	290
Lower Sind Barrage (2400' upstream of site B near Hajipur)—Experiments in connection with dissipation of energy downstream of—	•••	***	10-11	***	***
Lower Sind Barrage—Comparision of sites for the—	331	55	****	***	***
Lower Sind Barrage—Design of the—Experiments to test the design for scour and sand exclusion from canals—Sind.	***	***	48-59	98	***
Lower Sind Barrage—Experiments to determine a suitable profile of the—to cause minimum afflux with gates fully open.	set .		22-29	***	•••
Lower Sind Barrage, site C-island for	4 (***)	98			***
Lower Sind Barrage at Kotri—Factors affecting the exclusion of sand from the canals, at the proposed—			•••	105	•••
Lower Sind Barrage at Kotri—Scale ratios of the model.	***		•••	107	***
Lower Sind Barrage at Kotri-design of Lock Span.	(***)	••• s	***	***	191
Lowest hed levels in the Bukkur-Rohri gorge at Landsdowne Bridge during 1928-1944.	101 .	103	100	•••	•••
Lunt River—How to control—where it is crossed by the Samadari—Raniwara Branch line on Jodhpur Railway.	***	3*	•••	53, 52	****

L & M	Pages	of Annu fo	al Repor		nical)
	1943	1944	1945	1946	1947.
Luni River Floods—Steps necessary to protect main line from Hyderabad to Luni Junction on Jodhpur Railway from—		3, 5	•••	3	•••
Luni River—Training of the—to prevent it damaging Jodhpur Railway line.		,	36-42	•••	
M				ě	
M. &S. M. Railway—Heavy runoff from a small catchment u/s of a bridge of the, on the Guntakal-Bezawada section of the—which caused the river to overflow the embankment and railway tract, causing an accident.	44	•••	•••		•••
Mahanadi anicut at Cuttack, Orissa-Kendrapara canal taking off Birupa river u/s of—how to prevent silting of—	(iii°)	•••	•••		•••
Mahanadi and Katjuri at Cuttack (Orissa)— Distribution of flood waters between—	37,38	, ·••	19-22		
Mahanadi group of rivers at Cuttack (Orissa)— How to control deterioration of the—	(iii)*	•••	•••	•••	
Mahanadi River—preventing scour below the central sluices of—at the Mahanadi Anicut at Cuttack (Orissa).	•••	***	***	5, 27	34
Mahanadi River—Test of measures to dissipate energy to prevent serious damage to the central sluices of— at Cuttack (Orissa).	***		1 - 1 -	31	
Mahanadi River—Calculations for the Standing Wave, Baffle pavement, etc.—proposed design to prevent damage to the central sluices of—at Cuttack (Orissa).			•••	36	
Mahanadi River—Redistribution of sand load between the Mahanadi & Katjuri river system at Cuttack (Orissa).			•••	44	35
Mahanadi River—Experiments with reduced and unreduced Naraj weir length to find the distribution of sand load between Mahanadi and Katjuri System.		•••	***	45	
Mahanadi Main canal Falls (C. P.)—coefficient of discharge of Notch type and Weir type Falls on	•••	•••			23
Major Gorie's Paper on soil denudation.	3		•••		·
Malaprabha river—Training the—to protect the left bank and aboutment of the M.&S. M. Ry. Bridge No. 8 at Hole-Alur on the Hotgi-Gadag line.		•••	7-8	* · . 5	7 7
Manas, Beki and Balkadoba rivers (Assam)— How to train and control—	(ii)*	3, 69, 70	•••	•••	
Mandeswari River.	·	13		. h.i.	
Maps— Rain Gauge Station maps of India, Burma and Ceylon.	\$11 1	***	***	162	,***

M	Pages of Annual Report (Technica for the year				nical)
	1943	1944	1945	1946	1947_
Marginal bunds of the Indus above Sukkur (Sind)—Realignment of the Rohri-Quetta Railway necessitated by the danger of breaches in the—	(ii)•	•••		•••	***
Maximum depth of scourat heads of guide banks and groynes, pier noses and d/s of Bridges.	•••	74	•••	•	•••
Maximum depth of scour at noses of guide banks, groynes and at sharp bends.		75, 83	•••	•••	•••
Maximum depth of scour related to V ² /d which is related to turbulence.	200	. 74	•••	•••	•••
Maximum depth of scour round piers of Bridges in-	e.				•
(a) the Brahmaputra at Amingaon;	•••	75, 82	•••	•••	***
(b) the Chenab at Alexandra Railway Bridge near Wazirabad (N. W. Rly.);	•••	,	•••	•••	***
(c) the Chenab at Chiniot (N. W. Rly.);		,,		***	•••
(d) the Chenab at Chund (N. W. Rly.);	•••	,,	•••	•••	
(e) the Chenab at Shershah (N. W. Rly.);		••	***		•••
(f) the Gandak Railway Bridge at Bagaha (O. & T. Rly.)		**	•••	•••	•
(g) the Ganges near the Hardinge Bridge (B. A. Rly.);	# * *	75, 82	••••		•••
(h) the Indus in Rohri—Bukkur gorge;		"			
(i) the Jhelum near Jhelum Railway Bridge (N. W. Rly.);		,,	•••	•••	•••
(j) the Jhelum near Shahpur (N. W. Rly.);		**	•••	•••	•••
(k) the Jumna Railway Bridge at Delhi;		ͺ"	•••	•••	•••
(1) the Karnaphuli Railway Bridge;	•••	75,78,82	•••	•••	•••
(m) the Meghna near Railway Bridge (B. A. Rly.);	•••	,,	•••	•••	•••
(n) the Par near Rly. Bridge (B. B. & C. I. Rly.);	***	••	•••	•••	. •••
(o) the Ravi near Rly. Bridge at Dera Baba Nanak(N. W. Rly.);		75,77,8 2	•••	***	•••
(p) the Sutlej near Empress Rly. Bridge at Adamwahan;		••	***		***
(q) the Sutlej near Rly. Bridge at Phillaur.	•••	••	•••	***	***
Maximum depth of scour at noses of guide banks, groynes and at sharp bends in—				•	·
(a) Ganga at Sara Guide bank, 3 miles u/s of the Hardinge Bridge;	***	75, 83	, •••	***	•••

M	Pages of Annual Report (Technical) for the year				
	1943	1944	1945	1946	1947.
(b) Ganga near the nose of the Right Guide Bank of the Hardinge Bridge;	•••	75,83	•••	•••	•••
(c) Hooghly near Dunbar Cotton Mill;	•••	"		•••	***
(d) Jumna near Delhi Gate Pumping Stn. at spur 5;	•••	,,	•••	•••	•••
(e) Narbada River, old Railway Bridge at Broach, B. B. & C. I. Rly.;	′	75, 77, 79, 83	•••	••• 1	•••
(f) Right Bank approach channel at Sukkur;	•••	75,77,83		•••	•••
(g) Ravi u/s of Balloki Weir— (i) at nose of spur 5 on the Right Bank; (ii) at nose of spur 6 on the Right Bank;		76,77,79 80, 83	• • • • • • • • • • • • • • • • • • •		
 (h) Sutlej at u/s of the Rly. Bridge, Ferozepore (N. W. Rly.) (i) at nose of spur 4; (ii) at nose of the old Right Guide Bank. 	•••	76, 77, 79, 83		indige in Line in Silver Line in Silver Lin Silver Lin Silver Lin	***
Maximum depth of scour d/s of bridges in— (a) the Ganga d/s of pier 3 of the Hardinge Bridge;	•••	76,77,83		•••	•••
(b) the N. W. Canal d/s of the Rly. Bridge near Ruk (N. W. Rly.);	•••	599 - 1	• • • • • • • • • • • • • • • • • • • •	•••	•••
(c) the Rice Canal d/s of the Rly. Bridge at R. D. 75, 000 (N. W. Rly.);	•••	•	•••	•••	•••
(d) the Rohri Canal d/s of the Rohri Multan Road Bridge at R. D. 52, 000;	•	76, 77, 81, 83	•••		• • • •
(e) the Rohri Canal d/s of the Head Regulator at Sukkur;	•••	76, 77, 80, 83	•••	•••	
(f) scour d/s of the Road Bridges on the Eastern Jumna Canal.	•••	76,77, 83	•••	•••;	
Maximum depth of scour d/s of Bridges.	•••	75,76,77 80,81,83	***	Mary , ata di Sa in a	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Maximum freshet ebb discharge in the Rupnarain River at Kolaghat Railway Bridge on the B. N. Rly. in 1944, estimation of		14	•••	•••	•••
Meandering of the River Sutlej between Ferozepore and Suleimanke Headworks.	(ii)*	•••	***		•••
Meander length of the Rupnarian River- Increase in the-due to increase in freshet discharge.	***	14	 ,	•••	•••
Meander lengths in pebble bed flumes.	50	•••			• * *
Meander Belt— probable maximum development to be allowed for, to prevent erosion of Railway embankment at the proposed C. K. Railway Bridge over Ramgana River.	••••	•••	, ***	6	•••

M	Pages of Annual Report (Technical)				ical)
	1943	1944	1945	1946	1947.
Meandering of Rivers factors determining the size and shape of	•••	•••	•••	131	•••
Measures to prevent bank erosion at the Rup- narian Bridge near Kolaghat on the B. N. Railway in Bengal.	•••	3, 13	•••	***	***
Measures taken to control erosion of the left bank of the Rupnarian upstream of the Bengal Nagpur Railway Bridge at Kolaghat by means of deflecting groyne.	***	م	5-7	•••	•••
Mechanism of ripple formation.	53			•••	• •••
Methods followed in fixing model scale ratios and overcoming model limitations, based on experience gained at the Indian Waterways Experiment Station, Poona.	•••	•••	88- 116	•••	•••
Method of calculating scale ratios in vertically- Leexaggerated mobile river models.	•••	•••	107- 110	•••	***
Meyer Peter's & Schoklitsch's Bed load formulae & their comparison with station formulae.	49			٠	•••
Military Board set up in 1850 to study Damodar River flood and realignment of embankments.	•••	14	•••	•••	•••
Mississippi formula—use of—for estimating the maximum flood discharge in the Gandak River at Bagaha on the Oudh and Tirhut Railway in 1924.		12		•••	***
Mithrao and Khipro Canals—Control of sand entering, Ex-Nara at Makhi (Sind).	•••	.700	•••	127	***
Mobile river models, vertically exaggerated— Method of calculating scale ratios in—	•••	•••	107- 110	•••	***
Model Experiments—Field results of measures adopted after.	•••	•••	***	5	34
Model—Equivalent size and specific gravity of stones and blocks in a—	••• .	•••	115- 116	•••	•••
Model limitations—Methods followed in over- coming—and model scale ratios—methods followed in fixing—based on experience gained at the Indian Waterways Experiment Station, Poona.	•••	•••	86 <u>-</u> 116	•••	34
Model limitations—action of tree groynes as regards bank erosion and accretion upstream and downstream of the groynes.	•••	***	•••	5	•••
Model-Pilot & mobile bed-Experiments with	•••	15		•••	***
Model-reproduction of curvature in a-	59	•••	•••	•••	•••
Model scale ratios—methods followed in fixing—and model limitations—methods followed in overcoming—based on experience gained at the Indian Waterways Experiment Station, Loona.	•••	•••	88- 116	•••	***

M & N		al Report (Technical) or the year			
	1943	1944	1945	1946	1947.
Model—Scale Ratios of the Sutlej River model at Samasata Station—N. W. Railway.			•••	76	1.1 · •••
Model—Scale Ratios of the Lower Sind Barrage model on Indus River at Kotri.	***	, 44.	firee	107.	•••
Model Scale ratios—Time scale, based on trac- tive force formula used in Kotri Island nose experiments—Lower Sind Barrage.	•••	•••	***	110	404
Model (1/400, 1/66), vertically-exaggerated—of the Mahanadi and its Branches at Cuttack (Orissa)—Experiments with the	•••	•••	19–22	44	35
Model scale ratios of model of Kshipra River at Ujjain.	. •••	•••	14 :	••••	47
Model scale ratios of Tapti River at Surat—design of		•••		•••	58
Model scale ratios of Cochin Harbour—design of		•••	•••	•••	102
Models, geometrically-similar which give geo- metrically-similar results.	•••	•••	92	•••	
Models, geometrically-similar which do not give geometrically-similar results.	•••	•••	99–101	•••	•••
Models, rigid and vertically-exaggerated.		1	103	•••	•••
Models, semi-rigid and vertically exaggerated.			105	•	***
Model Experiments—Technique of	•••		***	142	5 · · · ·
Models, tidal—scale ratios of—			10 4 -105	111	
Models, vertically-exaggerated of rivers (tidal and non-tidal).	· `	•••	102	* ****	
Models vertically-exaggerated and mobile— Methods of calculating scale ratios in—		; ·	107110	•••	# - 4.
Moja—Damodar River.		31	** 0 B Z		
Motaguri Bund on the Manas River—Breaching		5			•••
Mud Banks—Report of the Special Committee 1938, on formation of Mud Bank at Cochin Harbour.	·:	•••			92
Mud Banks—at Cochin Harbour—movement	•••	•••		•••	112
		7854 E		,	1 2
N	*		2.5	!	
Nara—Eastern and Rohri canals (Sind) Fluc- tuation of grade of materials exposed on the beds of the—	35	•••	••• •••	***	•••
Naraj Weir at Cuttack (Orissa)—Standing wave and drowned condition of the—and their effect on the sand drawn by the Katjuri.	38			***	•••

N & O	Pages		nal Repo or the ye		nical)
s	1943	1944	1945	1946	1947.
Narbada River—Water levels of maximum floods in the—during 1886 to 1944.		85	***	•••	•••
Narbada, Tapti and Sabarmati Rivers—Preven- tion of erosion of agricultural lands along the—		2,3,5, 85		***	•••
Neamati in Assam—Prevention of erosion at—	,	3*			•••
Nira L. B. Canal Head Regulator—Coefficient of discharge of the—	· •••	•••	95	122	
Nira L. B. canal (Bombay)—Jeur aqueduct on the—Discharge formula for—	(ii)*	***	•••	•••	***
Nira Right Bank Canal Aqueduct No. 23— Fluming of	•••		٠	122	•••
Nomograms for determining commonly required hydraulic elements and constants.			78–80		
Nomograms—Punjab Irrigation—by Mr. E. S. Lindley.		. 6	•	•••	***
North Western Canal—Sukkur Barrage on Indus River—Flattening the slope of	•••	***		85	***
Number of dry days during which Tansa storage (Bombay) was depleted—years 1896-1944.		73			***
Number of wet days before depletion started in Tansa (Bombay)—years 1896 to 1944.		73	•••		
Nuna-Pothi rivers in Orissa—Flood protection measures for—		3*	•••		***
N. W. Canal in Sind—Prevention of scour below a bridge on the—		3	•••	•••	•••
N. W. Railway Bridge over the N. W. canal near Ruk, Sind—Deep scour d/s of the—experi- ments carried out to evolve a suitable design of pavement and side expansion to induce accretion.		23	•••	•••	
··· o	¥				
Offtake—Design of—at the entrance to the right pocket from the approach channel at Sukkur.	•••	•••	96	••	***
Orissa, experiments with a vertically exaggerated model (1/400, 1/66) of the Mahanadi and its branches at Cuttack.		•••	19-22	•••	•••
Orissa, Cuttack—Katjuri and Mahanadi group of rivers near—Experiments with a model of the		*	19	44	. 35
Orissa, Cuttack—How to control deterioration of the Mahanadi group of rivers in—	(iii)•			•••	•••
Orissa, Cuttack—How to prevent silting of Ken- drapara Canal taking off Birupa river, u/s of Mahanadi Anicut.	(iii) •		.,,,	•••	•••

0 & P	Pages		nal Repor		nical)
	1943	1944	1945	1946	1947.
Orissa, Cuttack-Mahanadi and Katjuri at- Distribution of flood waters between-	37		19		453
Orisea, Cuttack—Naraj weir at— Standing wave and drowned condition of the—and their effect on the sand drawn by the Katjuri.	. 38	•••	19	***	•••
Orissa—Flood protection measures for Nuna Pothi Rivers in—	,	3*	•••		
Orissa, Prevention of silt going into the Surada Reservoir at its Padma Intake in—	•••	. 2*	•••	•••	•••
Oudh and Tirhut Railway—Gandak River at Bagaha on the—which has outflanked the bridge—how to divert the—to its original course through the bridge.	(iii)*	` 10	a •••	s •••	•
P					
	es and a second	× * *	9		
Paharpur Canal and Bilot creek—Analysis of data of	32	***		***	160
Pebble bed flume—Experiments to see what changes occur when the charge of uniform bed material is suddenly increased.	50			•••	
Pebbles in pebble-bed filumes—Transportation of—	47	1 p p	•••	•••	•••
Periyar River—Dominant discharge of		1		11	105
Permissibility or otherwise of reducing spillway capacity, Berar (Akola Municipality).		2*			
Piers—depth of foundation of—for the proposed C. K. Railway Bridge over Ramaganga River.	•••			14	•••
Piers—maximum depth of scour at the nose of	***	ļ. 		140	
Piers—scour round the				129	310
Piles—Longitudinal and cross row of—at the knuckle at Dunbar cotton Mills to enable accretion and silting to take place.	364	7		39	****
Pilot Model and mobile bed model—Experiments with—		15		****	
Port of Rangoon Tidal Model.			107	***	
Positioning of 'attracting' islands as related to meander length.		97	<u> </u>	···	
Prediction of the future movement of the Gandak River at Bagaha.	•••	13			
Present and future water requirements and supplies in the Jumna at Delhi.	ļ	91		138	•••
Prevention of collapse of Rohri Multan Road Bridge over Rohri Canal at R. D. 52,000 in Sind.	•••	3*	****		

P	Pages of Annual Report for the year				nical)
	1943	1944	1945	1946	1947.
Prevention of damage to the Surat-Rander Road and the city wall of Surat d/s of the Hope Bridge from floods in the Tapti River in Gujarat.	•••	3, 6, 87		***	***
Preventing serious damage to the central sluices of Mahanadi Anicut at Cuttack (Orissa).		•••	•••	27	***
Prevention of erosion at Neamati in Assam.	***	3*	***	***	***
Prevention of erosion of agricultural lands along- the Tapti, Narbada and Sabarmati rivers.	•••	3, 5, 84	•••	•••	
Prevention of erosion on Bombay foreshore and reclamation of land bearing S. No. 71, part of Juhu and creek-land.	***	1•	•••	***	•••
Prevention of foreshore erosion at Visagapattam.		3*	•••	•••	***
Prevention of further erosion on the left bank of the Rupnarian river above Kolaghat Railway Bridge of the B. N. Railway.	•••	13	***	130	101
Prevention of further erosion of the left bank of Sutley River at Samasata Station, N. W. Rly.			- •••	68	•••
Prevention of erosion along the foreshore of the Hooghly River above Calcutta,	`	•••	***	130	•••
Prevention of further erosion of the left bank of Watrak River upstream of Kaira Town (Bombay).		•••	` •••	64	•••
Prevention of scour below a bridge on the N. W. Canal in Sind.	•••	3, 23	•••	•••	•••
Prevention of scour in Garang river on Assam access Road.		3*	•••		. •••
Prevention of scour below the central sluices of the Jobra Anicut on the Mahanadi at Cuttack (Orissa).		•••	•	5	•••
Prevention of sea wall erosion at Bombay.	•••	1•	•••	•••	•••
Prevention of silt going into the Surada Reservoir at its Padma Intake in Orissa.	•••	2*	•••	•••	***
Prevention of slips of the right bank of Indus below the nose of approach channel—upstream of Sukkur Barrage.				17	• •••
Proposal to construct a Barrage on Tank Zam in N. W. F. Province to split up water between several areas.	•••	2*	•••		
Proposals to prevent a recurrence of damage resulting from breaches in the Damodar river, Bengal.		.3*		•••	***
Proposed diversion of 40,000 cs. to relieve flooding at Gorakhpur on O. and T. Railway.		2*	•••		•••
Proportionality of discharge in S. W. F. s. and height of hump—Relation between		. 43	***	•••	•••

P, Q & R	Pages	t (Tech	nical)		
	1943	1944	1945	1946	1947.
Protection of Bridge over Rivers and Canals.			· •••	128	•••
Protection of the foreshore of the Anglo-India Jute Mill on the Hooghly (Bengal).	•••	•••		42	•••
Protection of retaining walls from scour by means of repelling spurs (Baluchistan),	# 44	***	8	• •••	
Protecting the toe of a retaining wall from scour, particularly on a curve, in South Quetta, Baluchistan.	***	1*	•••		•••
Protection to the piers of the Elgin Bridge over the Gogra River on O. and T. Railway.		1. 1.	***		
Protective measures below the new undersluices of Son at Dehri—Bihar officers' proposals tested in Model.		21	•••	•••	3414 172,111
Protective measures—Dehri (Bihar)—Optimum design of control blocks and deflectors.		21	••••	* ***	•••
Pump House—supply of sand free water to Jam- shedpur Pump House.		1 14.00 1 101	**************************************	•••	187
Pump House at Jamshedpur—design of intake tower.	 	**** ****		200 3 [*] 1444 [*]	188
Punjab Engineering Congress—Written discussion by Director on Paper No. 275 "River-training and control by pitched 'attracting' islands".	•••	97			***
Punjab Government—CHOS Act passed by the—for afforestation.	3		1		
Punjab Irrigation Nomograms by Mr. E. S. Lindley.	•••	6	•••	•••	•••
Punjab practice of constructing Headworks.	•••	98	•••	•••	•••
Punjab L. J. C., L. C. C., Jamrao canals and Sukkur Barrage Canals (Sind)—Relation- ship between area and discharge.	23	•••	748		***
Q					
Quetta-Rohri Railway—realignment of the, necessitated by the danger of breaches in the marginal bunds of the Indus above Sukkur	. (ii)*	•••	•••		• ••
R		Þ	7.	• .	• • •
Railway bridge d/s of Bagaha on the Gundak river—Proposed	13		•••	•••	•••
Railway Bridges—on Madras Bombay line of M. & S. M. Railway, between Miles 82 & 113; protective measures for			•••	•••	52
Rainfall and run-off in Indian catchments.	44, 67	68-		124,131	19
Rainfall and run-off in American catchments.	69		7.7	•••	

R	Pages of Annual Report (Techn for the year				
	1943	1944	1945	1946	1947.
Rainfall and run-off from Karamnasa river at Silhat weir, U. P.		68	•••	•••	
Rainfall and run-off—In the Upper Indus catchment—some features of precipitational variation in—	 .	, 	***	ņı	7
Rain Guage Station Maps of India, Burma and Ceylon.	;	184	•••	162	
Rajkot State—Run-off from Lalpuri Tank iu—	,	68		***	***
Rajkot State—Thorala catchments in—Maximum possible discharge from catchment of—	(ii)*	***	***		***
Ramganga River-probable maximum flood discharge of, at the C. K. Railway Bridge.	•••		• •••	10	•••
Ramganga River—design of Guide Banks for maximum depth of scour at the proposed C. K. Railway Bridge.	,	***		13	, , ,,
Ramganga River—Length of Guide Banks at the proposed C. K. Railway Bridge over	* ***	•••	~	15	•••
Ramganga River—maximum depth of scour and depth of foundations for the proposed C. K. Railway Bridge Piers over	••••	. ***		14	204
Rander Road—closing of spills on right bank u/s of Hope bridge near Surat led to heavy erosion of the—		88	1. 1. (1.1.1) 1.1.1	•••	¥ 1.00
Rangoon Port Tidal Model.		-444	107	•••	100
Rate of sand attrition in channels.	62, 64			115	***
Ratnagiri—Erosion at—how to improve conditions and prevent further—	(ii)*	•••	•••	***	•••
Recommendations of the Solani dam section based on model experiments.	***	63	•••	•••	***
Recovery of head, modular limit and range in S. W. Flumes,		37	***	***	*
Regeneration in the Jumna river.		93	•••	***	
Regime—Divergence from—in stable channels in alluvium.	•••	•••	· •••	135	•••
Relation between bulk proportionality and height of hump.		43		•••	,
Relation between floods in the Monsoon and regeneration in the Hot-weather in the Jumna River.		93	***	***	***
Relation between the mean rainfall at Wada and Bhivandi and Bombay water supply—1895 to 1944.		73	974	•••	
Relation between proportionality of discharge in S. W. F. 8 and height of hump.		43		•••	•••

R	Pages of Annual Report (Technical)					
	1943	1944	1945	1946	1947.	
Relation between the size of air pipe, size of the discharge pipe & the drum with leakage from shamber.	***	67		. j ••• ,		
Relationship between area and discharge of L. C. C., L. J. C. (Punjab), Jamrao canals & Sukkur Barrage canals (Sind).	23	•••				
Relation between mean depth and discharge per foot width of Jamrao and S. B. Canals (Sind).	24	•••	•••		••• •	
Relationship between S. & Q of Jamrao and Sukkur Barrage Canals.	26				•••	
Relationship between surface width and Q of Jamrao and Sukkur Barrage canals.	25	•••	2 ()	*	•	
Remodelling of Canals.		***		123		
Remodelling of Son Aniout at Dehri.	, *** .	20, 58		1,		
Remodelling Railway Bridge over the N. W. Canal at R. D. 75.000 on the N. W. Railway.	. ***	3,23	•••	* * * * * * * * * * * * * * * * * * *	***	
Remodelling the Rice canal in Head portion.	***	3, 104,		F14	•••	
Repelling groyne upstream of the Railway Bridge on the Rupnarian River at Kolaghat on B. N. Railway—comparison of results in the model and in the river.	•	18	•••			
Retaining walls from scour—Protection of—by means of repelling spurs (Baluchistan).	•••		8		***	
Revetment acts as 'attracting' groyne.		2, 104		•••	· · •••	
Review—Historical—of Steps taken by the Sind Government to collect data in connection with Indus and to control it in its passage through Sind.	11		ése.			
Rice Canal in head portion—Remodelling the—		3, 104	*****		•	
Rice Canal—Improvement of the—due to Right Bank approach channel at Sukkur.	35	•••		•••	•••	
Right Bank approach channel at Sukkur—Datum area 1,000 ft. d/s of Sukkur Barrage before and after the—was constructed.	,	102				
Right Bank Approach Channel at Sukkur— Improvement of the Rice canal due to—	33		•••	•••	•••	
Ripples and waves—classification of—	54					
Ripples and waves—Factors affecting the shape and dimensions of—	56	•••	***	•	***	
Ripples—Effect of size, distribution of particles, specific gravity, charge of bed sand and discharge on	57	•••	•••	- 1 - 100 - 2 - 1	e . April .	
Ripple formation—Mechanism of—	53.					

R	Pages of Annual Report (Technical for the year				
	1943	1944	1945	1946	1947.
Ripples to waves—Transition from—	55		•••	•••	***
Rivers and Canals—flow in	***	•••	•••	85	
River model Experiments—difficulties experi- enced in—due to effects caused by vertical exaggeration.	6 a	•••	110- 113		
Rigid structures in wide channels—Scour downstream of—	. •••	***	67 <u>-</u> 71	•••	***
Rigid, vertically-exaggerated models.		•••	103	•••	. •••
River floods—Sunspot intensity cycles as a medium of predicting the probable dates of occurrence of	***		86-87	•••	
	v.:				
River meandering—factors determining the size and shape of	***			181	
River Bunds in Sind—causes of breaches and steps required to minimise the danger of re-	•••			133	`•••
currence. River training and control by pitched islands.	***	97		::	
erior transfer and douttor of breamon interest				500	
River Training—the use of 'attracting' spurs and islands for—	- 47	97	•••	•••	***
Road Culverts—design of approaches & exists of	•••			37	***
Rohri & Eastern Nara Canals—Fluctuations of grade of materials exposed on the beds of the—	35	•••	***	***	•••
Rohri Canal (Sind)—Effect of closing the Head Regulator of the—from the top down- wards, on the canal Regimen.	35		•••	•••	•••
wards, on the caust megimen.					
Rohri—Erosion on the Right Bank of the Indus above—and danger of breach of the main line, N. W. Rly.	ˈ (ɪɪ)•	•••	***	*** ** **	,,,4
Rohri-Multan Road Bridge over Rohri Canal at R.D. 52,000 in Sind—Prevention of collapse of	• •••	3*	•••	•••	• •••
Ronri-Quetta Railway—realignment of the— necessitated by the danger of breaches in the marginal bunds of the Indus above Sukkur (Sind).	(ii)•	* 31-1		•••	•••
Run-off formulas—Emperical—	67			4	•••
Run-off from catchments in Ceylon—advice regarding probable maximum		2*	٠	•••	
Run-off from Lalpuri Tank in Rajkot State.	•••	68	•••	•••	•••
Run-off—Heavy, from a small catchment u/s of a bridge of the M. & S. M. Rly., which caused the river to overflow the embankment and railway track, causing an accident.	44	••••		•••	2 1.
Run-off, maximum flood and catchment area— Relation between—	67	•••		***	***

R&S	Pages of Annual Report (Technical) for the year				
A 1	1943	1944	1945	1946	1947.
Rupnarian Bridge near Kolaghat on the B. N. Railway in Bengal—Measures to prevent bank erosion at	***	3, 13	•••	78	
Rupnarian River u/s of the Kolaghat bridge on the B. N. Rly.—Causes leading to erosion of the left bank of the—	****	14		•••	
Rupnarian River u/s of the Kolaghat bridge on the B. N. Rly.,—Fair weather and freshet spring tides in the—in 1944 and in its mobile bed model.	•••	17, 20		· /	
Rupnarian River u/s of the Kholaghat bridge on the B. N. Rly.,—Maximum freshet ebb dis- charge in the— in 1944, estimation of	 }	14	2 444	***	
Rupnarian River u/s of the Kolaghat bridge on the B. N. Rly.,—Meander length of the— Increase in the—due to increase in freshet	•••	14	erei •••	•••	1 (,) 1 i i i i
discharge— Rupnarian River above Kolaghat Railway Bridge on the B. N. Railway—Prevention of	(iii)*	13	ing in the second	130	•
further erosion on the left bank of the— Rupnarian River above Kolaghat Railway Bridge on the B. N. Railway—Repelling groyne u/s of the Bridge—Comparison of results in the		18	· · · · · · · · · · · · · · · · · · ·	•••	
model and in the river. Rupnarian River above Kolaghat Railway Bridge on the B. N. Railway—Tidal Range of the—	•••	14	• • • •	•••	
Rupnarian u/s of the B. N. Railway Bridge at Kolaghat—Measures taken to control erosion of the left bank of the—by means of a deflecting groyne.	•••	•••	5–7	••••	
Ryve's Run-off formula.	67				20
8					
abarmati, Narbada and Tapti Rivers—Preven- tion of erosion of agricultural lands along the—	•••	2, 3, 5, 84	•••	***	
Sabarmati River—Water levels of maximum floods in the—during 1893 to 1944.		86	•••	•••	••
sagi River—Minimum waterways required for— Jodhpur Railway Bridge.	. •••	•••	***	37	
akri River project (Bihar).	្រុះ			en.	199
amasata spur on Sutlej river on the N. W. Railway to prevent dangerous erosion.	***	3*, 5	•••	•••	•••
and and silt on the bed of the Rupnarain River at Kolaghat Railway Bridge on the B. N. Rly.	•••	16	100 111 15 12 1	to eng So este So en e eng	, 2
Sand attrition—rate of—in channels.	62			444	¥ 100 1

8	. Pages	t (Tech	nical)		
	1943	1944	1945	1946	1947
Sand-exclusion and soour from canals—Sind. Experiments to test the design for		•••	48-59	•••	•••
Sand-exclusion—at the nose of the outer Bank and at the raised sill of approach channel with and without outer Bank extension.		•••	•••	•••	177
Sand-exclusion of sand from the canals at the proposed Lower Sind Barrage on Indus at Kotri.	•••	•••	•••	105	116
Sand—design of air sand-meter.				**4	32
Sand—mechanical analysis of by Puri sand- meter and Air sand-meter.		***	•••	***	26
Sand-wind Tunnel classifier for sand and silt.		•••	, •••	•••	28
Sand particles—movement of	53	•••	•••	***	•••
Sand—Entering R. B. Canals at Sukkur—Control of, by means of approach channel.		***	•••	126	***
Sand excluding heads for the M. E. canal and M. W. Canal on the Son at Dehri (Bihar).		58		127	***
Sand Load—Redistribution of-between Mahanadi River and Katjuri River System at Cuttack (Orissa).		•••	19	44	35
Sand—Rate of attrition of, in rivers and canals.	 	•••		115	•••
Sangli State-Desilting and dredging Tanks in-		2*		•••	
Saturation line—effect of constructing a trench on the		61	•••	•••	***
Saturation line or hydraulic gradient—effect of variation of u/s and d/s water levels of the Solani Khadir dam model on—		61	•••	•••	
Scale ratios—Methods of calculating—in vertically-exaggerated mobile river models.			107 <u>–</u> 110	•••	,
Scale ratios of tidal model.			104-105	•••	
Scale ratios of the Sutlej River model—experiments with satlej river model at Samasata Station—N. W. Railway.			•••	76	•
Scale ratios of Lower Sind Barrage model on Indus river at Kotri.		•••	•••	107	•••
Schoklitsch's and Meyer Peter's Bed Load formula and their comparison with Station formula.	49	•••	•••	•••	•••
Scour and accretion in models and rivers compared with special reference to islands u/s of the Barrage.		99	•••	•••	•••
Scour and sand exclusion from canals, Sind— Experiments to test the design for—		•••	48–59	540	•••

s	Pages of Annual Report (Technical) for the year					
	1943	1944	1945	1946	1947.	
Scour below a bridge on the N. W. canal in Sind-Prevention of-	°	3 ,23	•••	•••	₩,	
Scour below the central sluices of the Johra Anicut on Mahanadi at Cuttack (Orissa).	•••	•••	• •••	5, 27	34	
Scour below weirs.		74	67	114	67	
Scour—Depth of scour in river downstream, with Ganesh Iyer Volute Siphon Spillways.	•••			91	165-	
Scour downstream of rigid structures in wide channels.	* 44. 5		67-71	114	69	
Scour around the nose of the right bank approach channel at Sukkur.		74	•••	•••		
Scour at spurs in river models.		74	. '***	•••	***	
Scour downstream of flumed falls.			97		67	
Scour d/s of the Sarda Barrage at Banbassa (U. P.)—Prevention of		•••	•••	24		
Scour-hole—Reproduction of—in a model, downstream of Hardinge Bridge piers 2 and 3.	,	74	***	•••	•••	
Scour-hole d/s of the Hardinge Bridge.	,	74			***	
Scour-hole, 47 ft. deep, just d/s of the Head Regulator of the Rohri Canal.		74		•••		
Scour-hole, 35 ft. deep, just d/s of the Road Bridge at R. D. 52,000 of the Robri Canal, which threatened to undermine the bridge.	•	74	••••	. •••		
Scour-hole, in the canal bed and bellied banks d/s of the railway Bridge on the Rice Canal at R. D. 74944.	***	74	* 411	***	***	
Scour-hole d/s of the N. W. Rly. bridge at Ruk over the N. W. canal—conditions leading to—		23	***	•••	***	
Scour-hole—Approximate quantity of stone required for filling the-in the Approach Channel and constructing a pitched truncated nose at Sukkur Barrage.		***		26		
Scour-holes of the present under-sluices of the Son at Dehri (Bihar).	***	20	•••	****		
Scour in Garang River on Assam Access Road— Prevention of	•••	3*	•••	***		
Scour—optimum shape of the island at the pro- posed lower Sind Barrage at Kotri to get minimum scour at the nose of the island.	**** 3	•••	•••	112	***	
Scour below Kotri Barrage		,		•••	72	
Scour round divide wall noses-Kotri.	l				73.	

s	Pages of Annual Report (Technifor the year				mical)
	1943	1944	1945	1946	1947.
Scour—Prevention of, d/s of sluices of the Son Anicat at Debri.	•••	. 20		•••	•••
Scour round bridge piers.	* 100	•••	814	129	***
Scour-model limitation of tree groyne action in reproducing bank erosion and accretion u/s and d/s.	114	***	•••	5	***
Scour—maximum depth of, at heads of guide bank and groynes, pier noses and d/s of bridges.	te#	•••	•••	, 140	70
Scour—maximum depth of, at the truncated nose, Indus River above Sukkur Barrage for designing the apron.	•••	***	***	24	
Scouring of channels—factors affecting	•••	•••	***	132	
Scouring of tail channel and regulation, at Sukkur.	•••	***	•••		61
Sea wall erosion at Bombay-Prevention of	•••	1•		•••	***
Semi-rigid, vertically-exaggerated models.;	***	•••	105	***	
Sewage-Poona Sewage disposal by irrigation of	***	•••	***	123	•••
Shape and dimensions of ripples and waves— Factors affecting the	56	, ,		•••	***
Shape of catchment—effect of—on the run-off	•••	68	•••	•••	20
Shape of channels—factors affecting the	22	544		•••	***
Silting and scouring of channels—factors affecting the, Note for the Orissa flood Advisory Committee on our present knowledge of the	•••	•••	***	132	•••
Silt in suspension at Sukkur and Kotri since 1913—Quality of	19	•••	•••	•••	
Silt—Prevention of—going into the Surada Reservoir at its Padma Intake in Orissa.	in	2*	***	•••	
Sind—Analysis of Inundation canals in—and its comparison with the data of perennial canals,	344 ·	- 29-32	***		, ***
Sind—areas flooded as a result of breaches in embankments in—during the 1942 flood season.	•••	11	•••	***	
Sind—Breaches in the Indus in—How to Prevent.	20	•••	•••	•••	•••
Sind—Causes of floods in	12			••••	•••
Sind—Design of canals in— Part I—New Canals. Part II—Inundation Canals.	21	•••		•••	•••
Sind—Design of lower Sind Barrage at Hajipur.	(ii)	55	• • •	•••	•••

8	Pages of Annual Report (Technifor the year				
	1943	1944	1945	1946	1947.
ind Government—Historical review of steps taken by the—to collect data in connection with the Indus and to control it in its passage through Sind.	11	•••	•		•
ind—Indus at Sukkur—New factors which will affect the rate of rise of water levels in the	17	***	•••	•••	
ind—Indus—Effect of constructing a barrage accross a river on bed levels and water levels u/s and d/s with particular reference to the	18	99	***	•••	
ind—Iudus in—Technical analysis of the avail- able data regarding the rise of water levels of the-in the past and to be anticipated in future.	15	•••			
ind—Jamshoro Bund on the left bank of the Indus near Hyderabad.	39	***	•••	,••• !	
ind—Prevention of collapse of Rohri-Multan Road Bridge over Rohri Canal of R. D. 52,000 in	•••	3*	***	;•••.	•••
ind—Rate of rise of water level in the Indus in	15		•••	****	
ind—Remodelling Railway Bridge over the N. W. Canal at R. D. 75,000 on the N. W. Rly.	•••	3, 23	****	•••	4
ind—Remodelling the Rice Canal in head portion.		; 3		· · · · · ·	
ind—Rohri canal—Effect of closing the head regulator of the—from the top downwards on the canal regimen.	35	•	•••	•••	
ind—specific discharge gauge at Bachalshah on the Indus in	•••	101	•••	•••	•••
iphons—volute—originated and designed by Mr. Ganesh Iyer—Experiments to improve the design of	(ii)* .	•••			,
iphon spillways		•••	97-98	141	1 * 1 7. 2
iphon spillways: Ganesh Iyer's volute siphon—Factors affecting the coefficient of discharge of			72–78	•••	
iphon Spillways—preventing scour below- Ganesh Iyer Volute Siphon by mutual impact of jets.	•••			91	165
iphon Spillway in Jodhpur State—Erinpura Irrigation and Hydro-electrical Project.		2*	***	•••	•••
lope—design of canals—slopes in perennial and inundation canals in Sind.			•••	136	
lloping groynes, above the old Riy. bridge on the Narbada River at Broach.		. 85			

S	Pages of Annual Report (Tech for the year				
<u></u>	1943	1944	1945	1946	1947.
Soil classification and demarcation of block area in Bombay Deccan.		•••	***	121	•••
Soil surveys in Sind.		•••		123	***
Soil denudation—Excess sand charge due to	5	413			¥ 94-
Solani Dam—Recommendations of the—based on model experiments.	* ***	63	•••	***	***
Solani Dam-staunching due to silting u/s of the-effect of	y ***	63	•••	***	
Solani embankment—Leakage through		63		•••	
Solani Khadir and Balta Jheel reservoirs in the U. P.—model experiments in connection with	•••	59		•••	•••
Solani Khadir and Balta Jheel (U. P.)—whether material is suitable for constructing a dam in the	(iii)*	***	•>=	,	***
Solani Khadir Dam model—effect of variation of u/s and d/s water levels of the—on hydraulic gradient or saturation line.		61		,	* ***-
Solani Khadir Dam Project—Special features of	•••	60	•••	***	•••
Solani soil-Transmission coefficient of the	***	63		•••	***
Son Anicut at Debri (Bibar)—Present method of regulation of—on rising flood and falling flood.	40		•••	••• •	•••
Son Anicut (Bihar)—sand reducing heads for the M. E. and M. W. Canals u/s of—	(iii) •	58	•••	•••	***
Son at Dehri (Bihar)—Optimum design of control blocks and deflectors.	 '	21.	•••	•••	•••
Son at Dehri (Bihar)—Protective measures below the new undersluices.	usen (B	20, 23		546 12	***
Son at Dehri (Bihar)—Remodelling the anicut.		***		127	***
Son at Dehri (Bibar)—Scour-hole downstream of the present undersluices of—		20		***	***
Son at Debri-Protective measures below the new undersluices of—Bihar Officers' proposals tested in Model.		21	•••	415-6 2	•••
Son River at Dehri (Bihar)—Sand drawn by the Canals and undersluices u/s of the anicut.	41	***		***	•••
Special features of the Solani Khadir dam project.		60	•••	•••	•••
Specific discharge gauges at Bachalshah on the Indus, Sind.	•••	101	•••	•••	•••
Specific gravity and equivalent size of stones and blocks in a model.	•••	•••	115-116	***	•••

	Pages of Annual Report (Technical)					
S	for the year					
	1943	1944	1945	1946	1947.	
Spillways—Siphon	* ***			141	***	
Spur 6 at Tajewala Headworks acts as an 'attracting' spur.	****	97		•••	***	
Spurs—attracting and repelling	47	97				
Spurs—' attracting '—in the Beas River.	(ii)•		;	•••	***	
Spurs—Control of the Jumna River at Tajewala—by means of—	(ii)*		•••		•••	
Spurs—the use of 'attracting'—for training a river, u/s of a masoury work—	47	97			•••	
Standing Wave Flumes—Coefficient of discharge of	•••	34	92-93	•••		
Standing Wave Flume—Controlled Irrigation.				122		
Standing Wave Flume—design of—for the Jawai River Project (Jodhpur).				86		
Standing Wave Flume—Water surface profiles in a 5' wide S. W. F. with parallel sides at various stages.	••••	•••		.86	•	
Standing Wave Flume discharge coefficient— Effect of piers on, in Sind falls.	***.	•••	94	•••	•••	
Standing Wave : Flumes—Effect of friction on coefficient of discharge.	v.; •••	47		•••	•••	
Standing Wave Flumes—Effect of piers on coefficient of discharge of—	::1	48	. •••		•••	
Standing Wave Flumes-Parallel flow through the throat of-		31	•••	•••	i ,	
Standing Wave Flumes—Recovery of head, modular limit, and range in—	¢	37			•••	
Standing Wave Flumes—Standard designs of—		49				
Standing Wave Flumes—Trapezoidal	***	34			• • •	
Standing Wave Flumes and Flume Meter Baffle Falls—design of—		29	. * * * *		,	
Standing Wave Flumes and falls—discharge Table of	•••	33	•••	***		
Standing Wave Flumes and Falls. U/s gauge and gauge chambers—Position of—		32	•••		•••	
Standing Wave Flumes and Falls—Velocity of approach—effect of—	****	33	•••		•••	
Standing Wave Flume—curvature of flow in the throat of a			80–85		f. *	
Staunching due to silting u/s of the Solani Dam—effect of—		63	•••			

S&T	Pages		nual Report (Technical) for the year				
	1943	1944	1945	1946	1947.		
Statistical analysis of past and future supplies available in the Jumna at the Headworks of the Eastern and Western Jumna canals at Tajewala and at Delhi.	•••	6, 9L	***		***		
Stone wall built to protect a palace acts as attracting groyne and holds the river permanently along the face.	·	104	***	•••	***		
Submerged spurs to enable accretion and silting to take place in the scour-hole d/s of the knuckle at Dunbar Cotton Mills.		. 7			***		
Sukkur Barrage—Afflux due to proposed extension of the outer bank of Approach Channel upstream of Sukkur Barrage over Indus.	***	•••	***	25	117		
Sukkur Barrage Canals (Sind), L. C. C., L. J. C. (Punjab) and Jamrso canals—Relationship between area and discharge—	23	•••	***	•••	****		
Sukkur Barrage canals and Jamrao canals— Relationship between surface width and Q.	24		•••	•••	•••		
Sukkur Barrage canals—Relationship between S and Q.	26			•••	***		
Sukkur Barrage—Causes of accretion of the river bed at—and how to reduce rate of rise, Part II.	•••	•••	59-66	137	•••		
Sukkur—Canals at—Right and Left bank, dif- ference in the behaviour of—	21	***		•••	***		
Sukkur Barrage—Mid-season scouring opera- tion of the right pocket at	·	•••	•••	•••	61		
Sukri Biver—Minimum waterway required for— Jodhpur Railway Bridge over	•••	•••		37	•••		
Sunspot intensity cycles as a medium of predicting the probable dates of occurrence of river floods.	•••		86–87	•••	***		
Surat-Rander Road and the City wall of Surat d/s of the Hope Bridge at Surat—Damage in 1944 to—and recommendations to ameliorate present conditions.	***	37	,	•••	***		
Surging over baffle wall,		30		***	•••		
Sutlej River—Meandering of the—between Ferozepore and Suleimanke Headworks.	(ii)*	•••	•••	•••	•••		
Sutlej River at Samasata d/s of the Empress Bridge at Adamwahan N. W. Railway— Training of		•	, 	68	•••		
Sutlej River—Training of the river with permeable tree groynes.	•••	•*•	***	78	***.		
T							
Tajewa'a—Control of the Jumna River at—by means of spurs.	(ii)*	•••	•••				

T	Page		ual Repo or the ye		mical)
	1943	1944	1945	1946	1947.
Tajewala—Headworks of Eastern and Western Jumna canals at—	•••	13		, y •••	•••
Tansa Dam—Determination of the coefficient of discharge of the automatic gates spillway for the—	•••,	•••	29-36	•••	153
Tapti, Narbada and Sabarmati Rivers—Preven- tion of erosion of agricultural lands along the—		3, 5, 84	•••	***	54
Tapti River—Water levels of maximum floods in the—during 1872 to 1944.	•••	84	•••	•••	•••
Technical analysis of available data regarding the rise of water levels of the Indus in the past and to be anticipated in future—	15	99	•••		***
Technical enquiry into the causes of breaches in River Bunds in Sind and steps required to minimize the danger of recurrence	20	•••	•••	•••	
Thorala Tank (in Rajkot State)—Maximum possible discharge from catchment of,	(ii)*	•••	•••	•••	f.
Tidal models—scale ratios of—	•••	•••	104-107	•••	•••
Tidal range of the Rupnarain River at Kolaghat Railway Bridge on the B. N. Railway.	•••	14	•••		•••
Tons and Giri catchments—effect of storages in—on supplies in the Jumna during flood season & regeneration in the fair season.	•••	94	•*•	•••	
Tractive force formula—used in fixing time scale of Kotri island model—Lower Sind Barrage on Indus.	•••	****	•••	110	
Tortuosity—Arc to chord ratio of Sutlej river loop at Samasata Station, N. W. Railway.	•••	· •••	₹ 200, ••• 100 100	69	•••
Training a river upstream of a masonry work— The use of 'attracting' spurs for—	47	•••	•••	•••	## # #40 •
Training of Luni River to prevent it damaging Jodhpur Railway line	• •••	•••	36–42	***	3. 1 9 ₽••
Training of Jumna River at Delhi Gate Pumping Station with pitched embankment on the right bank.	•••	•••	43-48	440	••• •••
Training the Hooghly River at Dunbar Cotton Mill with a by-pass channel.	•••	•••	11–18	•••	राहा । ••• राष्ट्री च कि
Training the Jumna at New Delhi Gate Pumping Station.	(iii)*	3	•••	•••	147.28 7 7
Training the Khari River so as to prevent out- flanking of the pick-up weir and Head Regu- lator of the Khari-out canal, and damage to Raipur village in Ahmedabad District.	•••	.2*	•••	•••	e e t ••• construction of
Training the Malaprabha River to protect the left bank & abutment of the M. & S. M. Rly. Bridge No. 8 at Hole-alur on the Hotgi-Gadag line. 12	•••		7-8		• • •

T, U, & V	Pages		al Repor		nical)
	1943	1944	1945	1946	1947,
Training the river Kshipra near Ujjain in Gwalior State.		2, 5	•••	***	
Training works at Dingra ghat on the Mahananda river in Bengal.		2*	•••		•••
Transmission Coefficient of sand sample from the bed of Damodar River at Sindri.	,	·	•••	94	•••
Transmission coefficients of the Solani soil.	٠	63			,
Tree-Groynes—semi-permeable tree groynes, to reduce risk of attack on the goods yard, Kolaghat Station upstream of B. N. Railway Bridge—Rupnarain River.	•	• • •••	•••	78	***
Tube well-yield from, in the Zhob valley, Baluchistan.			•••	97	540-
Tube wells—yield in relation to sub-soil.			· · · · · ·	94	
Turbulence—Reduction of, in the River Hoo- ghly downstream of the knuckle at the Tita- ghar Jute Mill (Bengal).		***	·	38	83:
Types of models.			88	,,,	***
υ	,			300 1	
Ujjain—Erosion of Kshipra River at—control of—	(ii)*	2*, 5	:"	•••	***
United Provinces—Balta and Solani Khadir—whether material available is suitable for constructing a dam in the—	(iii)*		••• ?,	###. 	s ::
Y					•
Vanes—submerged, to exclude sand from ca- nals at Lower Sind Barrage on the Indus at Kotri.			•••	. 101	•••
Vertically-exaggerated, models of rivers (tidal and non-tidal),			102	•••	•••
Vertically-exaggerated model (1/400, 1/66) of the Mahanadi and its branches at Cuttack (Orissa)—Experiments with the—	•		19-22	,	***
Vortically-exaggerated and semirigid models.			105	•••	***
Vertically-exaggerated and rigid models.	•••		103		100
Vertical exaggeration—Difficulties experienced in river model experiements due to effects caused by—	•••	•••	110–113	•••	***
Vertically-exaggerated mobile river models— method of calculating scale ratios in			107-110	•••	***
Vizgapatam—Prevention of foreshore erosion at—		3*	. •••	•••	•••
Volute siphon, Gamesh Lyar's—factors affecting the coefficient of discharge of—		·	72-78	•••	100

W	Page	Pages of Annual Report, (Technical) for the year				
	1943	1944	1945	1946	1947.	
Waste weir—Experiments with half size model of automatic gates on Tansa—				•••	153	
Water levels of maximum floods in the Nar- bada river during 1886 to 1944.	•••	85	***		•••	
Water levels of maximum floods in the Sabar- mati river during 1893 to 1944.		86	•••	•••	•••	
Water levels of maximum floods in the Tapti river during 1872 to 1944.	• •••	84	, ••••	•••	•••	
Water supply, possibilities of—to Cutch State from Indus River.		•••	•••	•••	219	
Water supply—Bombay city—augmentation of—		70				
Water supply, Delhi—Jumna River training in connection with—	(iii)*	8, 9	•••	•••		
Waterway—minimum for bridge over Sagi, Khara and Sukri Rivers—Jodhpur Railway.			•••	37	•••	
Watrak River—Training the, to protect Kaira, town, Gujerat (Bombay Presidency).				64	***	
Watrak River—Tree groynes to prevent further erosion of left bank at Kaira Town.				64	•••	
Wave crest—Phenomenon at the—	. 57				•••	
Wave crest—scour of the u/s slope of the—	- 57	•••	:			
Waves—How to reduce—in a dock caused by swell in harbour.	. 66			•••	`. -	
Waves and ripples—classification of—	55	•:•		***	•••	
Waves and ripples—Factors affecting the shape and dimensions of—	. 56	•••				
Waves—Ripples to—Transition from—	55	•••			•••	
Wazirabad—Alexandra Bridge over the Chenab River near—steps required to prevent damage to the Bailway Embankment of the—	(i) •	•••		•••		
Water requirments at Delhi.		91	,	***	•••	
Waterlogging—Dangers of—in the Eastern Nara tract in Khairpur State in Sind.	,	3*		•••	***	
Waterway of bridges in Ceylon—advice regarding		2*		***		
Waves in a model—apparatus for generating—in a model.	66	. ***	•••	***	***	
Weeds—water weeds and their eradication from canals.	***	•••	>>+	124	•••	
Weirs, high coefficient	ا		99-101	141		

W, Y, & Z	Pages of Annual Report (Technical) for the year				
	1943	1 1944	1945	1946	1947.
Weir-High Coefficient weir profile (Hydera- bad-Deccan).	. ,		•••	86	•••
Weir—Scour below weirs.	. 1**		***		. 67
Working range of baffles.		41			
Y	• 1.				
Yield during monsoon from Tansa catchment— years 1896 to 1944.		73	***		
z	s " s	•			
Zam Tank in N. W. F. Province—Proposal to construct a Barrage on—to split up water b etween several areas.	· ;"";	2*	•••		•••

<u>__</u>\$___