

IWE. 3-1
2,000

Government of India

CENTRAL WATERPOWER IRRIGATION & NAVIGATION
RESEARCH STATION, POONA.



RESEARCH PUBLICATION No. 13

**"THE BEHAVIOUR AND CONTROL
OF RIVERS AND CANALS
(WITH THE AID OF MODELS)."**

Part I

BY

Sir Claude Cavendish Inglis, C.I.E., B.A., B.A.I., M.I.C.E.,
M. Am.Soc.C.E., M.I.E. (I).

(In charge of Hydrodynamic Research at Poona from 1920-45 ; Director of the Indian Waterways Experiment Station from 1936-45 ; appointed Director, Hydrodynamics Research Organisation of the Department of Scientific and Industrial Research, London, England, March 1947).

D26,8:4:P.2

H9.1

D26,8:4:P.2
H9.1
057936

POONA
PRINTED AT THE YERAVDA PRISON PRESS, 1949.

Price: Rs. 16-8-0 or 25 sh. 6 d.
(The price is inclusive of price of Part II.)

IWE. 3-1
2,000

Government of India

CENTRAL WATERPOWER IRRIGATION & NAVIGATION
RESEARCH STATION, POONA.



RESEARCH PUBLICATION No. 13

**"THE BEHAVIOUR AND CONTROL
OF RIVERS AND CANALS
(WITH THE AID OF MODELS)."**

Part I

BY

Sir Claude Cavendish Inglis, C.I.E., B.A., B.A.I., M.I.C.E.,
M. Am.Soc.C.E., M.I.E. (I).

(In charge of Hydrodynamic Research at Poona from 1920-45; Director of the Indian Waterways Experiment Station from 1936-45; appointed Director, Hydraulics Research Organisation of the Department of Scientific and Industrial Research, London, England, March 1947).

POONA

PRINTED AT THE YERAVDA PRISON PRESS, 1949.

**List of Research Publications of Central Waterpower Irrigation and Navigation
Research Station, (formerly Indian Waterways Experiment Station, Poona)
available for sale with the Manager of Publications, Delhi, and Agents**

Symbol No.	Research Publica- tion No.	Subject.	Price.	Year of Publica- tion.
IHR. 1-38	1	Annual Report of work done during 1937-38 by C. O. Inglis, A. R. Thomas, Rao Sahib D. V. Joglekar and staff at Khadakwasla.	7 8 0	1939
IHR. 1-39	2	Annual Report of work done during 1938-39 by same authors as in 1.	7 8 0	1940
IHR. 2	3	Note on "The theory, design and construction of Gibb Modules which, without moving parts, give a constant discharge within working limits irrespective variations in upstream and downstream water levels" by C. O. Inglis and Rao Sahib D. V. Joglekar.	8 8 0	1941
IHR. 1-40	4	Annual Report of work done during 1939-40 by C. O. Inglis, A. R. Thomas, Rao Sahib D. V. Joglekar and staff at Khadakwasla.	7 8 0	1941
IHR. 1-41	5	Annual Report (Technical) of work done during the year 1940-41 and index for 1937-41 by C. O. Inglis, A. R. Thomas, Rao Sahib D. V. Joglekar and staff at Khadakwasla.	7 8 0	1942
IHR. 1-42	6	Annual Report (Technical) of work done during the year 1941-42 by C. O. Inglis, J. S. Reid, Rao Bahadur D. V. Joglekar and staff at Khadakwasla.	7 8 0	1944
IHR. 1-43	7	Annual Report (Technical) of work done during the year 1942-43 by C. O. Inglis, J. S. Reid, Rao Bahadur D. V. Joglekar and staff at Khadakwasla.	7 8 0	1945
IHR. 1-44	8	Annual Report (Technical) of work done during the year 1943 by C. O. Inglis, Rao Bahadur D. V. Joglekar and staff at Khadakwasla.	7 8 0	1945
IHR. 1-45	9	Annual Report (Technical) of work done during the year 1944 by C. O. Inglis, Rao Bahadur D. V. Joglekar and staff at Khadakwasla.	7 8 0	1945
IWE. 1-45	10	Annual Report (Technical) of work done during the year 1945 by Rao Bahadur D. V. Joglekar and staff at Khadakwasla.	25 0 0	1948
IWE. 1-46	11	Annual Report (Technical) of work done during the year 1946 by K. K. Framji, Rao Bahadur D. V. Joglekar and staff at Khadakwasla.	7 8 0	1947
IWE. 1-47	12	Annual Report (Technical) of work done during the year 1947 by K. K. Framji, Rao Bahadur D. V. Joglekar and staff at Khadakwasla.	25 0 0	1948

**THE BEHAVIOUR AND CONTROL OF RIVERS AND CANALS
(WITH THE AID OF MODELS)**

CONTENTS



	Page.
SYMBOLS AND DEFINITIONS.	... 1
CHAPTER 1.—Introduction	... 35
CHAPTER 2.—Review of factors controlling flow in alluvial channels	... 85
CHAPTER 3.—Historical note on regime flow in channels in alluvium and divergence from regime.	95
CHAPTER 4.—Meandering of rivers.	... 143
CHAPTER 5.—Behaviour of rivers—as exemplified by the Indus in Sind	... 167
CHAPTER 6.—Exclusion of excess bed material from canals and distributaries	... 217
CHAPTER 7.—Factors affecting flow in alluvial channels—as exemplified by the dimensions of canals in Sind.	283
CHAPTER 8.—Maximum depth of scour at heads of guide banks and groynes, pier noses, and downstream of bridges.	327
CHAPTER 9.—The design of falling aprons	... 355
CHAPTER 10.—Control of rivers by guide banks and groynes	... 379
CHAPTER 11.—Fluming	... 387
CHAPTER 12.—Points worth considering when designing and remodelling canal and river works.	407
CHAPTER 13.—Methods followed in fixing model scale ratios and overcoming model limitations, based on experience gained at the Indian Waterways Experiment Station, Poona.	427
APPENDIX 1.—List of Bombay P. W. D. Technical Papers and Annual Reports of the I. W. E. S., Poona.	453
APPENDIX 2.—Bed ripples and bed dunes	... 459
APPENDIX 3.—Factors affecting exclusion of bed sand from canals taking off from alluvial rivers.	471
APPENDIX 4.—Equivalent size and specific gravity of stones and blocks in a model.	485
INDEX	

INDEX

A	Page number.	Figure number.	Photo Sheet number	Page number of Part
Accretion—Definition of—	...	(I)
" —Rice and North Western Canals	1-11, 8-89	46, 241
" —River Indus at Sukkur	1-88	75
" —Time scales different for scour and—	18-88 (vii)	450
Adjustments in rivers	9-09, 4-07	88, 159
Aflux—Definition of—	(xvi)	5
Ajmer-Mewar. Unprecedented flood in	19-05	409
Alluvial channels. Factors affecting flow in	Chapter 7	288
Alluvium, flow in. Lacey Papers of 1929 and 1938	8-08	98
Alternate layers of sand and clay, Apron laid on—	9-06	361
Amlewa Nedi (U. P. Kalai Bridge)—Maximum flood discharge in the—	12-05	409
Anathema. Groynes are usually—to river-training engineers.	10-01	—	—	379
" Training works long considered	12-01	407
Aner at Jaupus (U. P.)—Maximum flood discharge in the—	12-05	409
Annual Reports (Technical)	...	Appendix 1	...	458
Annual run-off from catchments	12-06	418
Approach Channel. Effect of—on N. W. Canal	7-08, 7-05	289, 290
" " Effect of—on Rice Canal	7-04, 7-05	289, 290
" " Effect of—on water levels	8-14, 8-08	189, 284
" 6-09	211
" " Mithrao Canal	8-14, 8-20,	6-17, 6-18,	6-4, 6-5	245, 259
" " Effect of—Sukkur	7-02	239
" " Right Bank—Sukkur	1-12, 8-07	...	6-1	51, 281
" " Outer bank of—	1-14, 8-1	...
Apron. Alternate layers of sand and clay laid in—	9-08	361
" Blow out in falling—	9-07	361
" Conditions under which a falling apron may fail	9-09	362
" Grade of stone required in—	9-12	370
" Launching of—	9-02	356
" Mixture of stone in—	Chapter 9	355
" 9-11	369
" Quantity of stone required in falling—	9-18	370
" Slope. Inclination of launched—	9-04	359
" Slip in falling—	9-07	361
" Reinforcing a fallen—	9-14	372
" Stones of mixed sizes in—	9-05, 9-06	360, 360
" Failure of Hardinge Bridge—	9-10	362
Aprons. Falling—	Chapter 9	335
Areas. Change in Datum—downstream of Barrage	5-18	5-12	...	184
" Change in sectional—for 800,000 cusecs	5-18	5-12	...	184
Attack reduced by attracting groynes	12-01	407

INDEX

A and B, etc.	Para. number.	Figure number.	Photo Sheet number.	Page number of Para.
Attraction of Lime Kankar	10-05	380
Attracting groynes	10-05	10-2	...	380
" Attack reduced by—	12-01	407
B				
B—bed width	(X)	2
Baffle. An obstruction to dissipate energy	1-1	...
Bogra. Model of Gandak River and Bridge at—	1-23	...	1-21	54
Baitarni River. Maximum flood of—	12-05	409
Baluchistan. Floods in—	12-05	409
Barrage. Effect of Upper Sind—on d/a water levels	5-19	203
Barrage. Lower Sind—	10-05	380
Barrage. Effect of—on charge entering canals	6-04	220
" Effect of heading up water at Sukkur—	5-06	172
" Lower Sind—recommendations	1-29	75
" Sukkur—Modifications recommended	1-07	45
Barshore and Termorgha (Baluchistan). Maximum flood discharge in the—	12-05	409
Beale's flood formula	...	12-3
Bed materials. Exclusion and ejection of—	Chapter 6	217
" movement. The main difficulty in mobile models	18-23	444
" ripples and bed dunes. Movement of—	Appendix 2	459
Bed-load distribution between off-takes	6-22	266
Bell bund	10-00, 10-02	379, 379
Benares. Ganges held along left bank by cut-off of lime Kankar at—	10-05	380
Bend. Interference with natural flow round a—	12-02	407
Benda. Maximum depth of scour at guide banks, groynes (or spurs) and sharp—	Table 8—II 8-05	321 347
Berm material	2-01	45
Bernoulli's theorem	11-00	387
Betwa (U. P. Perichs)—Maximum flood discharge in the—	12-05	409
Bilot Creek (Indus). Groynes to protect—	10-01	379
Blanketing. Definition of—	(iv)	5
"	2-13	91
Blasius formula for smooth stage boundary layer	8-23	180
Blanch T—Paper on "Turbulent flow theory from the viewpoint of an irrigation engineer from India", written for U. S. Bureau of Reclamation Library, Denver, Colorado, also in La Houille, Blanche "Th'orie de l'Ecoulement Turbulent".	8-22	180
Blanch T—and King C—Paper on "effect" of dynamic shape on Lacey relations", Annual Report (Tech.), C. B. I. (India), 1941.	8-22	180
Blanch T—Institution of Civil Engineers, Paper on "A Universal flow formula", Journal April, 1939.	8-22	180
Blocks. Equivalent size of—in models	Appendix 4	485
Blow-out in falling agroh	9-07	361
Bombay. List of Technical Papers	Appendix 1	458
" Presidency. Rainfall to run-off relation in Ghats catchments.	12-06	418

INDEX

B and C	Para. number.	Figure number.	Photo Sheet number.	Page No. of para.
Bose, Dr. N. K.—Ph.D., P. E. G. Paper 193 "Silt movement and design of channels."	3-03	93
Bose. Flow formulae of 1936	3-08	98
Boundary layer. Separation of—	1-17	...	1-17	62
Brahmani (Or see). Maximum flood discharge in the	12-05	409
Brahmaputra River. Model of—Bridge at Amingon.	1-22, 1-23	...	1-21	54, 54
Breaches. Prevention of—in river embankments in Sind...	1-27	70
Bridge piers. Maximum depths of scour round—	8-01 to 8-04	8-1 to 8-9	8-1	828 to 833
Buckley on Beleida equation for constant silt charge	3-28	138
Bukkur Gauge	Table 8-1	...	1-11	819
" Max. and min. flood levels	5-08	5-9	...	177
" Accretion in Gorge between Bukkur and Rohri	5-11
Bund, Bell	10-00, 10-02	879, 879
Bund Manual, Sind	5-28 (xvi)	206
C				
Canal. Eastern Nara—Variations in grade of bed material in—	7-06	290
" Jamrao—	8-15, 8-16	111, 118
" North Western—Effect of Approach Channel on	7-08, 7-05	289, 290
" Bias—Effect of Approach Channel on	7-04, 7-05	289, 290
" Rohri—Variations in grade of bed material in	7-08	290
Canals at Sukkur. Flat gradients of Left Bank	7-01	288
" at Sukkur. Steep gradients of Right Bank	7-01	288
Catchment formula. Inglis fan—	12-05	12-1, 2 and 8	...	409
Catchments. Annual run-off from—	12-06	418
" Cautley's flood run-off value for small—	12-05	409
" Inglis on run-off and floods of	12-05	409
Cautley's flood run-off value for small catchments	12-05	409
C. B. I. Paper No. 20 of 1939, Lacey's—	3-09	102
Channel at Sukkur. Effect of Approach—	7-02	289
" Definition of—	(xxxv)	6
" Sand—experiments	1-16	...	1-16	68
Channels. Factors affecting flow in alluvial—	Chapter 7.	283
" And shoals in tidal models	13-14	439
" E. W. Lane's Paper of 1935 on Stable—	8-06	100
Characteristics of rivers. Factor determining—	2-11, 2-12	90, 90
Charge. Definition of—	(xxv)	2
" Significance of weighted mean (\bar{X} , V_s)	3-13	98
" To enter an off-take. Unsound to induce an excess.	12-08	403
Charge, terminal velocity and grade—their effect on area, velocity, slope, shape and width of a channel.	3-24	136
Charge (X) and terminal velocity (V_s) and their effect on Lacey formulae as modified by Sir Claude Inglis.	3-24	136
Chenab (Alexander Bridge, Punjab)—Maximum flood discharge in the	12-05	409

INDEX

G and D	Page number.	Figure number.	Photo Sheet number.	Page No. of para.
Chenab (Khanki Bridge, Punjab)	13.05	400
" (Mazala, Punjab)	13.05	409
" (Rivas Bridge, Punjab)	13.06	409
" (Sher Shah Bridge, Punjab)	13.06	400
" Lower	3.15, 3.16	111, 119
Coefficient of discharge of remodelled Head Regulator of Nine L. B. Canal, Eigh—	13.06	491
Coefficient of discharge of Standing Wave Flumes	13.08	428
Coefficients. Lacey's early formulas with latest—	3.04	99
Commonsense not a guide to river behaviour	13.00	407
Concave submerged vene at Sukkur	1.11, 6.06	...	1—11	6; 230
Conclusions regarding hydrodynamic model experiments	13.39	453
Conditions under which a falling apron may fail	9.09	882
Confusion due to lack of precision in terminology	Symbols & Defn.
Continuity of progression of materials	8.10	88
Continuation. Width—Definition of	(ix)	5
" Length— "	(ix)	5
Control of rivers by repellent groyne	10.04	880
Coseys (Mohanpur Anicut, Bengal). Maximum flood discharge in the—	13.08	409
Crossing. Cross-over. Definition of	(xiii)	4
Curvature of flow (In many Chapters but sea especially)	6.00, 6.05 6.28	6—2 (a) to (d)	...	217, 220 288
Curvature of flow. Application of—to river training	10.08	880
" " flow associated with meanders—	10.08	880
" " flow. Effect of—on sand erosion	Appendix 8	...	A2—1 A3—2	471
Out-off. Definition of—	(xiii)	4
" Demonstration model of—	1.14	51
" Ratio. Definition of	(xiii)	5
Outtake, Orissa. Model of Mahanadi and Katjuri at—	1.94	...	1—92	64
D				
d=average depth = A/W	(ix)	2
D=a length characterising the effective depth of an alluvial channel—unless otherwise stated.	(v)	2
Damodar (Bengal). Maximum flood discharge in the	13.05	409
Damodar flood	13.05	12—5	...	409
Dasai River at Pahari (U. P.). Maximum flood discharge in the—	13.06	409
Datum area at Sukkur. Changes in—	5.13	5—19	...	184
Definitions. Symbols and—	Symbols & Defn.	...	1—8, 1—6	1
Deflector	1.06 and 1.09	...	1—9	40 & 46
Delta. Seaward extension of—	5.05	171
Demonstration models.	1.18	...	1—15	51
Density T-headed groynes	10.00 10.01	10-1	879 879
Deposition of silt	5.08	169

INDEX

D and E	Para. number.	Figure number.	Photo Sheet number.	Page number of Para.
Depths. Maximum—downstream of bridge piers ...	Table 8—III 8-06	8-10	...	822 848
" " of scour at guide banks, groynes (and spurs) and sharp bends ...	8-06 Table 8—II 8-01 8-04	847 821
" " of scour round bridge piers ...	Table 8—I 8-9	8-1	828, 833	819
Depth scale ratio ...	18-38	448
Deterioration due to heading up at a Barrage ...	6-06, 5-17	5-7	...	172, 201
Dicken's max. flood formulae ...	19-05	19-1	...	409
Difficulty. The main—in mobile models is bed movement... ...	18-23	444
Different scale ratios of rigid and non-rigid portions of vertically-exaggerated models. Necessity of— ...	18-38 (iv)	442
Discharge. Fluming to increase— ...	11-08 11-04	11-4 to 11-13	...	887, 888
" relation in canal system. Inglis on grade to— ...	8-15	111
" scale ratio ...	18-27	448
Discrepancies inherent in models ...	18-00	427
Distortion. Longitudinal— ...	18-36 (v)	450
" of flow ...	12-02	407
Distribution of bed-load between off-takes ...	6-22	266
Divergence from Lacey regime = $(f_{VB} f_{RA})^{\frac{1}{3}}$...	8-05	99
Divergence from regime. Inglis on— ...	8-14	107
" Introduction of measure of normality and—by Inglis ...	8-05	99
Divide wall excluder ...	8-13, 5-19	8-15, 8-16	1-10, 6-9	242, 257
Dominant discharge. Definition of— ...	ixxi	
" Effect of reduction of— ...	9-08, 5-18	88, 201
" discharge. Meander length determined by— ...	10-09	880
Downstream of bridge piers. Max. depth of scour— ...	8-06	8-10	...	248
Eastern Nara Canal feeds Jamrao, Mithrao, Khipro and Hirai Canals. ...	6-14	...	8-1 to 8-5	245
Canal takes off from Left Bank upstream of Sukkur Barrage. ...	6-14	...	8-1 to 8	248
Eastern Nara Canal. Variations of grade of bed material in— ...	7-06	290
Ejectors. Sand— ...	5-22, 6-26 6-29	904, 963 375
" Tunnel Type Sand— ...	6-02	919
Ekrak Tank (Bombay)—Maximum flood discharge in the— ...	13-05	409
Elsden. The late F. V.—initiated tunnel-type excluders ...	6-02, 6-23	219, 267
Elutriator. Sand—	2-3	...
Equilibrium. Definition of— ...	(xxix)	8
Equivalent size of stones and blocks in a model ...	Appendix 4	485
Erosion. Definition of— ...	(lxxii)	5
Erosion and its prevention ...	10-04	880
Eustatic rise of sea level ...	5-08	169

INDEX

E and F	Para. number.	Figure number.	Photo Sheet number.	Page number of Para.
Exaggerated. Vertically—(A) tidal and (B) river models ...	18-19	489
Exaggerated length of standing wave in a vertically-exaggerated model.	18-84 (iii)	448
Excess charge entering Mithrao Canal. Effect of temporary—	12-03	408
" Unsound to induce an—to enter an off-take...	12-03	408
" energy. Merits and demerits of Canal Falls and Regulators for absorbing—	12-04	408
" friction loss in rigid models	...	12-03	...	428
Excluders and ejectors. Relative merits of—	6-27, 6-80	275, 275
Excluders. Divide Wall—	...	6-19	6-15, 6-16	1-10, 6-3
" P. F. Haigh on—	...	6-25	...	267
" Open-type	...	6-03 to 6-19, 6-15	...	319 to 243, 245, 346
" 6-16	346
" Sand—	...	Chapter 6 Appendix 8	...	217 471
" Funnel-type, shingle—at Tajewala	...	6-24	...	267
" Tunnel type—	...	6-02 6-28 to 6-25, 6-27	...	219, 267 to 267 275
Exclusion. Additional—difficulties when Canals take off from both banks	6-28	6-4, 6-22 6-28	...	275
Exclusion of bed sand at Head of Dim Minor, Jamrao Canal, Sind.	1-15	...	1-16	51
" Effect of curvature of flow on sand—	...	Appendix 8	A8-1 A8-2	471
" of bed sand from Canals, factors affecting—	...	Appendix 3 Chapter 6	A8-1 to A8-14	471 217
Experience. Importance of field—in mobile investigations	1-81	76
F				
$f_{vb} : f_{bs} : f_m : Q$ relation in a canal system	8-16	119
Facilities available at Poona Research Station	1-02	86
Factors affecting exclusion of bed sand	Appendix 8	...	A8-1, A8-2	471
" affecting flow in alluvial channels	...	Chapter 7	...	283
Failure of Hardinge Bridge aprons	9-10	...	9-2	362
Fall. Remodelling of Tando Mastikan	1-06	40
Falling aprons	...	Chapter 9	...	365
" apron. Conditions under which a—may fail	9-09	362
Falls and Regulators for absorbing excess energy. Merits and demerits of—	12-04	408
" Design of Flume meter—	...	1-06	...	40
" Scour downstream of flumed—	...	12-09	...	432
Fan catchment formula. Inglis'—	12-05	12-1, 2 and 3	...	409
Field inspection. Importance of—	1-81	76
Fish-like movement of sand particles	...	(ix)	...	476
Flared siphon outlet. Increased discharge due to—	12-10	433
Flat gradients of Left Bank Canals at Sutkurn	7-01	283
Flexible design? Foolproof or—	12-00	407
Flood formula, Beale's—	12-3	...
" Dicken's—	...	12-05	12-1	...
" Gutmann's—	12-3	...
" Inglis' fan catchment—	...	12-05	12-1, 2 and 3	409
" Khangar and Gulhati's—	12-3	...

INDEX

F and G.	Para. number.	Figure number.	Photo Sheet number.	Page number of Para.
Flood formula Ryve's—	12-05	12-1	...	409
" Whiting's—	...	12-1
" levels. Progressive rise of—in alluvial rivers	...	5-07
" of Balterni River. Maximum—	12-05	409
" Unprecedented—in Kharji River in Ajmere-Marwara	12-05	409
" run-off value for small catchments. Cautley's	12-05	409
Floods. Damodar—	12-05	12-5	...	409
" Girna—	12-05	12-4	...	409
" Son—	12-05	409
" in Baluchistan	12-05	409
" of catchments. Inglis on Run-off and—	12-05	409
Flow. Distortion of—	12-02	407
" Bose's—formula of 1936	8-08	98
" Factors affecting—in alluvial channels	Chapter 7	288
" Historical Note on regime—	Chapter 8	95
" Lacey Papers of 1919 and 1933 on—in alluvium	8-02	96
" round a bend. Interference with natural—	12-02	407
Fluctuating discharges. Effects of—	Chapter 11	887
Fluming.	Chapter 11	887
" to attain modularity	11-01	11-1	...	887
" increase discharge	11-03, 11-04	11-4 to 11-15	...	887
" reduce cost	11-02	...	11-1	887
" of masonry works	1-04	40
Flume. Standing Wave—	1-04	40
Foolproof or flexible designs?	12-00	407
Formulae of 1919. Lindley's—	8-01	95
" 1936. Bose's—	8-03	99
" with latest co-efficients Lacey's—	8-04	99
$F = \text{Froude number} = V^2/gD$ in terms of depth	(xix)	2
$Fr = \text{Froude number} = V^2/gW$ in terms of width	(xix)	2
Francis Spring. Sir—	Chapter 9	855
Friction loss in rigid models	9-11	369
" Excess—	13-85	419
Friedkin's Vicksburg meander experiments	4-05	151
Froude number	13-13	430
G				
$g = \text{gravity}$	(xviii)	2
Gandak River	12-28	444
" at Bagaha. Model of—	1-28	...	1-21, 1-13	54
Gangen (U. P.) Maximum flood discharge in the—	12-05	409
Ganges. Hardinge Bridge over—				
" Experiments and recommendations	1-19, 10-02	53, 379
" Hardinge Bridge. Models of—	1-19	...	1-18	53

INDEX

G	Para. number.	Figure number.	Photo Sheet number.	Page number of Para.
Ganges held along Left Bank at Benares by outcrop of Lime Kankar.	10-05	380
Ganges (U. P., Raiwala) Maximum flood discharge in the—	12-05	409
Gauges (U. P., Raiwala)	12-05	409
Garni (U. P., Karman)	12-05	409
Geometrically-similar models giving similar results	13-02 to 13-04	428 to 430
Geometrically-similar models not giving similar results	13-05	431
Geometrically-similar models which give partly geometrically similar and partly dissimilar results.	13-10	433
Ghat catchments, Bombay Presidency.		•		
Rainfall to run-off relation in—	13-06	446
Ghatprabha at Dhupdal Weir (Bombay).				
Maximum flood discharge in the—	13-05	409
Gibb module	1-1	...
Gibson. Professor A. H.—	13-10	433
Girna floods	12-05	12-4	...	409
Girna near Malegaon, Nasik (Bombay).				
Maximum flood discharge in the—	12-05	409
Godavari at Nandur-Madhmeshwar (Bombay).				
Maximum flood discharge in the—	12-05	409
Gordon A	1-82	77
Gorga. Progressive accretion in—3 miles upstream of Sukkur Barrage between Rohri and Bukkur Island.	5-13	5-11	...	184
Grade of bed material in Eastern Nara Canal. Variations in—	7-06	265
" " Material in Rohri Canal. Variations in—	7-06	290
" " materials exposed on channel beds	Symbol and Defs.
" " Effect of reduction in—	Chapter 2	86
Grade, charge and terminal velocity—their effect on area, velocity, slope, shape, and width of a channel.	8-24	186
Grade of Stone required in falling aprons	9-12	370
" to discharge relation in a canal system. Inglin on	8-15	111
Gradients, Flat—of Left Bank Canals at Sukkur	7-01	283
" Steep—of Right Bank Canals at Sukkur	7-01	283
Groynes, Attack reduced by attracting—	12-01	407
" are usually anathema to river training engineer	10-01	379
" Attracting—	10-05	10-2	...	380
" Dency T-headed—	10-00	379
Misuse of—	10-01	10-1	...	379
" or spurs. Maximum depth of scour at—	8-05	447
Table 8-II		821
" Repelling—	10-04	380
" to protect Bilot Creek, Indus	10-01	379
Guide Banks				
10-00	379
10-03	379
" Maximum depth of scour at—	8-05	347 351
Table—II		
Gulbati's flood formula. Khangar and—	12-3
Guttmann's flood formula	12-8

INDEX

H, I and J	Para. number	Figure number	Photo sheet number	Page number of para.
H				
Haligh F. P.—on excluders and ejectors	6-25 6-27	267 275
Harcourt Vernon	13-19	439
Hardinge Bridge Aprons, Failure of—	9-10	9-3	...	369
" " Experiments and recommendations	1-19	53
" " over Ganges	10-2	379
Hathmati at Klimatzagar (Bombay). Maximum flood discharge in the—	12-05	409
Hawes C. S.	1-82, 2-01	77, 85
Heading-up. Definition of—	(vii)	5
Hickin S. B., Construction of Approach Channel at Sukkur	6-09	241
High coefficient of discharge of remodelled Head Regulator of Nira L. R. Canal	13-05	431
High coefficient weirs	1-17 15-11	...	1-17	59 434
" level sill for excluding sand	6-11, 18-07	242 431
" sill offtake from Sukkur Approach Channel to exclude bed sand from Right Bank Canals	6-07, 18-07	...	6-1	251 431
Historical note on regime flow	Chapter III	95
Hooghly Tidal Model	1-25	...	1-28	68
Hydrodynamic model experimentation. Conclusions regarding—	13-83	451
I				
Inclination of launched apron slope	9-04	359
Incorrect throw-off in vertically-exaggerated models	13-23	447
India. Groynes to protect Bilot Creek	10-01	379
India (Attock, N. W. F. P.) Maximum flood discharge in the—	12-05	409
" (Ghazighat, N. W. F. P.) Maximum flood discharge in the—	12-05	409
" (Kalabagh, N. W. F. P.) Maximum flood discharge in the—	12-05	409
Inglis' discussion on Dr. Boss's P. E. C. Paper	8-05	99
" fan catchment formula	12-05	12-1, 2 and 3	...	409
Inglis on f_{VA} : f_{BS} : f_M : Q relations in a canal system	8-18	119
" " Introduction of measure of normality and divergence from regime	8-05	99
" " Grade: discharge relation in a canal system...	8-15	111
" " $m \propto Q^{1/2}$ relation in a canal system	8-15	111
" " run-off and floods of catchments	12-05	409
" " Paper on "Divergence from Regime".	8-14	107
" " meanders and their bearing on river training', Maritime and Waterways Paper No. 7, Inst. of C. E.	8-24	196
Inherent discrepancies in models	12-00	427
Instability of flow. Occur due to—	12-09	432
Interference with natural flow round a bend	12-02	407
Irrigation Development and Research Circle. Work done by	1-08 5-08	36 169
Isostatic depression	
J				
Jamrao Canal	8-15, 8-16	111, 119

INDEX

J, K and L	Para number	Figure number	Photo sheet number	Page number of Para.
Jawai River at Erinpura (Jodhpur State). Maximum flood discharge in the—	12-05	409
Jetting downstream of Bukkan Barrage	1-9	...
Jhelum. Lower—Canal	3-15, 8-16	111, 119
Jhelum (Kohala, Punjab) Maximum flood discharge in the—	12-05	409
" (Mangala, Punjab). Maximum flood discharge in the—	12-05	409
" (Rasul, Punjab). Maximum flood discharge in the—	12-05	409
Jumna (U. r., Faizabad) Maximum flood discharge in the—	12-05	409
K				
Kadwa at Palkhed (Bombay). Maximum flood discharge in the—	12-05	409
Kaire. Erosion of bank by Wotrak River at—	1-20	...
Karak Lora (Baluchistan) Maximum flood discharge in the—	12-05	409
Kalabagh tunnel-type excluder	...	6-21(b)
Kankar. Attraction of lime—	10-05	880
Karmansha (Silhat Weir, U. P.) Maximum flood discharge in the—	12-05	409
(Deodari, U. P.)	12-05	409
Katjuri River at Cuttack. Model of—	1-22
Kennedy's formula 1895	8-90	95
Kou (U. P., Gangan). Maximum flood discharge in the—	12-05	409
Khadakwasla Dam, Lake Pali (site of C. I. & H. R. S. later L. W. E. S.).	Frontispiece.
Khaisar River (Baluchistan). Maximum flood discharge in the—	12-05	409
Khangar and Gulhati's flood formula	...	12-8
Khanki tunnel-type excluder, designed and constructed by the late H. W. Nicholson	6-28	6-20	...	267
Khari River in Ajmere-Merwara. Unprecedented flood in—	12-05	409
Khipro Canal (See Mithrao Canal)	6-20	258
Kho (U. P. Headworks). Maximum flood discharge in the—	12-05	409
King C and Blanch T—Paper on "Effect of dynamic shape on Lacey relations" Annual Report (Tech), C. B. I. (India), 1941	3-22	180
King G. Paper on "Practical design formulae for stable irrigation channels" Annual Report (Tech), C. B. I. (India), 1943	3-22	190
King's Vanes for excluding sand	6-18	6-18, 6-14	6-3	246
Koti Bridge. Thickness of stone at—	9-11	368
Koyana at Helwak (Bombay). Maximum flood discharge in the—	12-05	409
L				
Lacey. Gerald—	1-82, 2-02, 3-08, 8-02, 8-00	77, 86, 87, 96, 327.
Lacey's C. B. I. Paper No. 20 of 1939	8-09	103
" discussion on Lane's Paper	8-07	100,
" " " White's "	8-12	107
" early formulae with latest coefficients	8-04	99

INDEX

L and M	Para number.	Figure number.	Photo sheet number.	Page number of Para.
Lacey's Papers of 1929 and 1933 on flow in alluvium	8.02	95
,, "shock theory"	9.10	102
Lacey G.—Paper on "A general theory of flow in alluvium" journal Institution of Civil Engineers, November 1946, Paper No. 5518.	8.83	193
Leipuri Tank (Rajkot State). Maximum flood discharge in the—	12.05	469
Lane, E. W.—Paper of 1935 on "Stable Channels".	8.06	100
Lane's reply to discussion	8.08	101
,, Paper. Lacey's discussion on—	8.07	100
Launched apron slope. Inclination of—	9.04	359
,, stone. Thickness of—on slope	9.11	363
Launching of an apron	9.02	356
Layers of sand and clay. Apron laid on alternate—	9.08	361
Lehri—Khamwan River (Baluchistan). Maximum flood discharge in the—	12.05	409
Length. Exaggerated—				
,, of standing wave in vertically-exaggerated model	13.34 (iii)	448
,, Scale ratios of—	13.35	445
Lindley's formulae of 1919	9.01	95
Lime Kankar. Attraction of—	10.05	380
Limitation of models	1.31, 13.39	451
Lines of flow at offtakes	13.03	6-2	...	492
List of Annual Reports (Technical)	Appendix 1	469
,, Bombay P. W. D. Technical Papers	Appendix 1	468
Longitudinal distortion	13.36 (v)	460
Lower Chenab Canal.	8.15, 8.16	111, 119
,, Jhelum Canal	8.15, 8.16	111, 119
,, Sind Barrage..	10.05	380
M				
m = weighted mean diameter in mm.	(xxvi)	2
$m_1 Q \propto Q$ in a canal system (Inglis)	9.15	111
Mahanadi River Model	1.24	...	1-22	64
Mahanadi (Narej Weir, Orissa). Maximum flood discharge in the—	12.05	409
Makhi Regulator. See Eastern Nara and Mithrao	1-15	...
Maleprahha. Model of Bridge over—at Hol-Alur (M. & S. M. Railway)	1-15	...
Malhotra, Dr.—on "shock theory"	8.14	107
Maximum depth of scour round bridges	8.01, 8.04, Table 8-1	8.1 to 8.9	8-1	328, 388, 319
Maximum flood formulae	12.05	409
,, of Baitarni River	12.05	409
Meander experiments	4.03	149
,, length determined by dominant discharge	10.03	380
Meandering of Rivers	See Chapter 4	149

INDEX

M and N	Para. number.	Figure number.	Photo sheet number.	Page number of para.
Meanders. Adjustments to meet varying river conditions—	4.07	153
"Comparison of—in river models	4.04	150
"Conditions giving rise to—	4.06	152
"Curvature of flow associated with—	10.03	380
"Definitions of—	(xxxvii) to (xl)	4 to 6
"Factors affecting—	4.01	143
"Field data	4.03	144
"Vicksburg experiments	4.05	151
"Meanders and their bearing on river training" by Ingla, Maritime and Waterways Paper No. 7, Inst. of C. E.	3.24	196
Misuse of groynes	...	12.01	...	407
Mithaco Approach Channel	6.14, 6.20	6-12 6-18	6-2 to 6-5	245, 258
"Canal. Effects of temporary excess charge in—	12.03	408
" Exclusion of bed sand from—	6.14 to 6.20	6-12 6-18	6-2 to 6-5	245 to 258
Mixed sizes of stone in aprons	9.05, 9.06, 9.11	360, 360, 36
Mobile stones models. Vertically-exaggerated—	12.23	444
Models. Conclusions regarding—	12.39	451
"Discrepancies inherent in river—	12.00, 12.39	427, 451
"Equivalent sizes of stones and blocks in—	Appendix 4	485
"Exaggerated length of standing wave in vertically-exaggerated—	12.34 (iii)	448
"Excess friction loss in rigid—	12.35	449
"Incorrect throw off in vertically-exaggerated—	12.33	447
"Necessity of different scale ratios of rigid and non-rigid portions in vertically-exaggerated—	12.35 (iv)	449
"Rigid tidal—	12.15, 12.16	441
"Rivers—	12.21	443
"Semi-rigid tidal—	12.17 to 12.20	441 to 442
"Vertically-exaggerated rigid river—	12.21	443
"Vertically-exaggerated mobile river—	12.23	444
"Vertically-exaggerated (A) tidal and (B) river—	12.12	439
Modularity. Fluming to attain—	11.01	11-1	...	387
Movement of bed ripples and bed dunes	Appendix 2	459
"Bed—The main difficulty in mobile models	12.23	444
Mula-Mutha at Jamsetji Bund, Poona (Bombay). Maximum flood discharge in the—	12.05	409
Mula at Chikalthan (Bombay). Maximum flood discharge in the—	12.05	409
Mula at Bahuri (Bombay). Maximum flood discharge in the—	12.05	409
Mula at Tae (Bombay). Maximum flood discharge in the—	12.05	409
Mutha at Khadakwasla Dam (Bombay). Maximum flood discharge in the—	12.05	409
N				
Nala upstream of M. & S. M. Railway Bridge, 445 (Guntakal-Borwada Section-mile 453). Maximum flood discharge in the—	12.05	409

INDEX

N, O and P.	Para. Number	Figure Number	Photo Sheet No.	Page No. of Para.
$N = \text{Coefficient of rugosity with subscript if necessary}$ $K = \text{Kutter. } M = \text{Manning}$	(xxii)	2
$N_a = \text{Lacey's coefficient of rugosity } N_a = \frac{1.346}{V} R^{\frac{1}{6}} S^{\frac{1}{2}}$	(xxiii)	2
Nara. Eastern—Canal	6.14	245
" " Variations in grade of bed material	7.06	390
Nataj Weir. "Tilting" of—	18.87 (vi)	460
Nari Rivers (Baluchistan)—Maximum flood discharge in the—	12.05	409
Natural flow round a bend. Interference with—	13.03	407
Nature's way of excluding sand	6.03	219
Necessity of different scale ratios of rigid and non-rigid portions of vertically-exaggerated models.	18.85 (iv)	449
Nicholson, H. W.	1.89, 5.18, 6.28, 6.80	77, 201 267, 275
Nile at Beleida. Phillips equation for the—	8.28	139
Nira at Vir (Bombay). Maximum flood discharge in the—	12.05	409
Nira Left Bank Canal. Head Regulator. Effect of re-modelling of—	11.04	888
Nira Left Bank Canal. High coefficient of discharge of remodelled Head Regulator of—	18.05	431
Normality and divergence in flow by Inglis	8.65	99
North Western Canal. Effect of Approach Channel on—	7.08, 7.05	289, 290
North Western Canal. Effect of depth of sand on bed of—	6.09	6—8	...	941
North Western Canal at Sukkur	1.12	51
O				
Object of Report on the Behaviour and Control of Canals and Rivers.	1.01	55
Oderolal Regulator	1—10	...
Off-take. High sill—from Approach Channel at Sukkur to exclude sand.	13.07 6.07	431, 231
Off-take. Lines of flow at an—	18.08	6—9	...	482
One-man stone. Thickness of launched apron of—	9.11	366
One-man stone	9.11	366
Open-flow. <i>See</i> Still-pond.	6.19	6—16	6—8	207
Osborne Reynolds	18.19 18.18	489 489
Outer bank of Approach Channel	1—14	...
Outfall. Gauge at—cross-section	...	6—6 (6)
P				
$P = \text{wetted perimeter}$...	(vi)	...	2
Paharpur Canal	10.01	879
Panjhra near Nahaled (Bombay). Maximum flood discharge in the—	12.05	409
Panjhra near Madhi Amalner (Bombay). Maximum flood discharge in the—	12.05	469
Parat Nala (G.P. & Berar). Maximum flood discharge in the—	12.05	409
Pavement. Modification of—at Sukkur Barrage	1.07	45
Phillips equation—for the Nile at Beleida	8.28	181

INDEX

P, Q and R	Para. number.	Figure number.	Photo sheet number.	Page No. of Para.
Piers. Maximum depth of scour round bridge—	8.01-8.04 Table 8-I	8-1 to 8-9	8-1 to 8-9	826, 838 319
" Maximum depth of scour downstream of bridge—	8.06 Table 8-III	8-10	...	848 822
" Models of Sukkur Barrage—	1.08	...	1-8	45
Ponding. Definition of—	(xviii)	5
" Effect of—on water levels upstream	5.06	173
Poonah (Punjab) Maximum flood discharge in the—	12.05	419
Pravara at Ojhar (Bombay) Maximum flood discharge in the—	12.05	409
Precision in terminology. Confusion due to lack of—	Symbols & Defs.
Q				
Q =Discharge in cusecs	(i)
q =Discharge per ft. width	(ia)	3
Quantity of stone required in falling aprons	9.18	370
B				
R =Hydraulic mean depth=A/P	(vii)
Re =Reynolds number=(VD)/ γ	(xiv)
Rainfall. Relations in Ghat catchments (Bombay Presidencies) between—and run-off.	12.06	418
B/S ; S	8.13	107
Ratios. Scale—in vertically-exaggerated models	13.94 to 13.91	445 to 447
Ratnau (U. P., Dhanapur). Maximum flood discharge in the—	12.05	409
Rayleigh	12.14	439
Rayleigh's wave relation $V_w = \sqrt{gd}$	12.14	439
Reach. Definition of—	(xxxvi)
Recession of valleys	5.05	171
Reduction. Effect of—of charge	5.18	201
" " " discharge	5.18	201
" " " grade	5.18	201
" Cause of—in silt charge at Sagar and Kotri.	5.21	203
Regime and Stability	Symbols and Defs.
" flow. Historical note on—	Chapter 8.	95
" Inglis on divergence from—	8.14	107
" Lacey's definition.	2.02	86
" Lacey—formulae	2.03	87
Regulator. Effect of remodelling Nira Left Bank Canal Head—	11.04	888
Regulators for absorbing excess energy. Merits and demerits of—	12.04	408
Reinforcing a fallen apron	9.14	372
Remodelling. Effect of—Nira Left Bank Canal Head Regulator,	11.04	888
Remodelling. Effect of—pavement of Sukkur Barrage	1.07	45

INDEX

R and S.	Para. number	Figure number	Photo sheet number	Page No. of Para.
Repelling groynes above B. N. Railway Bridge over Rupnaraain.	10.04	880
Control of river by—	10.04	880
Reports. List of Annual Technical—	Appendix 1	458
Retrogression. Definition of—	(xiv)	5
of water levels at Sukkur	5.09	178
Sympathetic—	5.18	201
Reynolds, Osborne—	13.12	439
"	13.18	439
"	19.12	439
"	19.13	439
Rice Canal, Sind. Accretion in—overcome	7.04	289
" " Depth of sand on bed of—	6.09	6-8	...	241
" " Effect of Approach Channel on—	7.04, 7.05	289, 290
Rigid river models. Vertically-exaggerated—	13.21	448
Rigid tidal models. Vertically-exaggerated—	13.15	441
"	13.16	441
Ripple movement	2.10	2-2	2-1	88
Ripple turbulence	2.04	87
Ripples. Movement of bed—and bed dunes!	Appendix 2	459
Rise of water levels due to Sukkur Barrage	5.09, 5.10,	5-10	...	178, 182
River. Application of curvature of flow to—training	10.03	880
River. Experiments with—models	13.39	451
River models. See Chapter 13	13.21	449
River training engineers. Groynes are usually anathema to—	10.01	879
River Training—"Meanders and their bearing", by Inglis, Maritime and Waterways Paper No. 7, Inst. of C. E.	3.24	158
River. Vertically-exaggerated rigid—models	13.22	448
Rivers. Professor G. M. White's Paper of 1939 "The Influence of Transported Solids on—"	8.11	102
Rohri Canal. Variations of grade of bed material in—	7.06	290
Run-off and floods of catchments. Inglis on—	12.05	409
" from catchments. Relation of Annual—to rainfall in Chat catchment, Bombay Presidency	12.06	418
Rupnaraain. B. N. Railway over—	10.04	880
" model	1.28	1-24	...	78
" Repelling groyne above—	10.04	880
" Ryve's maximum flood formula	12.05	12-1	...	409
S				
S = slope = energy gradient	(xii)	9
S* = slope per 1,000 ft.	(xiii)	3
S* V; Ra S*	3.13	107
Salberg F. J. Discussion by—on Rupnaraain model	10.01	879, 407
Sand channel experiments	12.01	52
" Sand excluding sill	1.16	1-16	...	52
Sand exclusion. Effect of curvature of flow on—	6.07, 6.16	6-5, 6-7 (a)	1-16	281, 246
	Appendix 3	...	A8-1, A8-2	471

INDEX

S	Para. number.	Figure number.	Photo sheet number.	Page No. of Para.
Sand. Factors affecting exclusion of bed—	Appendix 3	...	A8-1, A8-2 6-1	471
Sand from Right Bank Canals. High sill off-take from Approach Channel at Sukkur to exclude bed—	8-07, 18-07	...	281, 481	
Sand=material >0.10 mm. and <0.60 mm.	2-01	85
Sand movement	2-10 (d)	2-3	...	90
Sand Scale ratio of—in models	18-31	447
Sanding=deposition of sand	(iii)	5
Sanda Bridge. Thickness of stone at—	9-11	368
Sarwa River. Model of groyne in—at Banbassa, to protect Right Aflux Bund.	1-20	...	1-19	54
	1-17	53
Scale effect	...			
" ratio. Depth—	18-28	448
" " Discharge—	18-27	445
" " in vertically-exaggerated models	18-24 to 18-31	445 to 447
" " Length—	18-25	445
" " Sand—	18-31	447
" " Slope—	18-39	448
" " Time—	18-30	447
" " Width—	18-26	445
Scale ratios of rigid and non-rigid portions of vertically-exaggerated models. Necessity of different—	13-85 (iv)	449
Scour—	Chapter 9	355
" and accretion. Time scales different for—	13-88 (vi)	450
" definition of—	(iv)	5
" downstream of flumed falls	13-09	432
" due to instability of flow	18-09	432
" Maximum depth of—downstream of bridge piers	8-08	8-10	...	348
		Table 8—III		329
" Maximum depth of—round bridges	8-01, 8-04	8-1 to 8-9	8-1	328, 333
" Maximum depth of—at guide banks, groynes (or spurs) and sharp bends.	Table 8—I 8-05	319 347
		Table 8—I		321
Semi-rigid tidal models	18-17, 19-18, 18-19, 19-20	441, 442 442, 443
" vertically-exaggerated models	18-12	439
Sheet movement	9-08	88
Shock theory. Lacey's—	8-10	102
" " Dr. Malhotra on Lacey's—	8-14	107
Shoals and channels in tidal models	18-14	439
Short spur at Banbassa to protect Right Aflux Bund	1-19	...
Siluria Nala (O.P. & Berar). Maximum flood discharge in the—	18-05	409
Sill. High—off-take from Approach Channel at Sukkur to exclude excess bed sand from Right Bank Canals.	8-07, 18-07	281, 481
Silt, silting.	Symbols & Defn.
" charge. Progressive reduction of—at Sukkur	5-16, 5-21	5-15, 5-16	...	189, 203
" and sand exclusion	6-10	6-5, 6-7(a)	1-16	242
Silting. Definition of—	(i)	6-10	...	5

INDEX

S	Para. number.	Figure number.	Photo sheet number.	Page No. of Para.
Silting in Right Bank Canals, Sukkur	1-05	40
Similar. Geometrically-similar models which give partly—and partly dissimilar results, siphon spillways.	18-10	433
Similar results. Models giving geometrically—	18-02 to 18-04	438 to 439
Sind Barrage. Lower—	10-05	880
Siphon. Increased discharge due to adding flared outlet—	18-10	433
Siphon spillways	Frontispiece	...
" " Geometrically-similar models give partly similar and partly dissimilar results.	18-10	438
Size of stones and blocks. Equivalent—to be used in models	Appendix 4	435
Slips in falling aprons	9-07	861
Slope exaggeration. Definition of—	(iii)	5
" scale ratio	18-29	448
Son at Dehri. Exclusion of sand from—	6-28	875
" Maximum flood in—River	12-05	409
Son (Bihar, Dehri). Maximum flood discharge in the—	12-05	409
Special Irrigation Division. Work done by—	1-08	86
Specific discharge gauge reading. Definition of—	(xxxii)	8
" discharge gauge reading downstream of Sukkur Barrage	5-09	5-10	...	178
" discharge gauge reading. Short period variations in—	5-15	5-19, 5-14	...	189
Spring. Sir Francis—	Chapter 9 10-00, 10-02	855 879
" " "—" " River Training and Control on the Guide Bank System " G. of I. Ry. Board T. P. 153 (1908).	10-00	879
Spurs and sharp bands. Maximum depth of scour at guide banks, groynes (or —)	8-05 Table 8-II	847 831
Stability. Definition of—	(xxx)	8
" Regime and—
Stable channels. E. W. Lane's Paper of 1935 on—	8-06	100
Standing wave. Enforcement of—	1-09	...	1-8, 1-4 1-8 to 1-9	46
" " flumes at Sukkur Barrage	18-06	431
" " flumes	1-2 to 1-6	...
" " Coefficient of discharge of—	18-08	428
" " in vertically-exaggerated model. Exaggerated length of—	18-34 (iii)	448
Steep gradients of Right Bank Canals at Sukkur	7-01	288, 287
Still pond—see open flow	6-19	6-16	6-8	...
Stone. One man—	9-11	868
" Mixture of—of various sizes in apron	9-11	868
" Thickness of launched—on slope	9-11	868
" Thickness of—at Kosi Bridge	9-11	868
" Thickness of—at Sarda Bridge	9-11	868
Stones. Equivalent size of—in models	Appendix 4	435
" of mixed sizes in aprons	9-05, 9-06	860, 860
" Quantity of—required in falling aprons	9-13	870

INDEX

S and T.	Para. number	Figure number	Photo Sheet number	Page number of Para.
Submerged vane. Exclusion by means of a—	1.11, 6.06 6.17	...	1--11	46, 220 246
Sukkur Barrage. Causes of accretion at—	... 1.11	46
" " Approach Channel to—	1.12	51
" " Modification of downstream pavement of— to exclude excess sand.	1.07	45
" " Position of standing wave at—	18.06	481
" " Rice and N. W. Canal (Right Bank) at—	1.05	40
" " Rise of water levels at—due to accretion ...	5.09, 5.10	5--10	...	178, 182
" " Rohri and E. Nara Canals (Left Bank) ...	7.01	288
" " Specific discharge gauge readings down- stream of—	5.09	5--10	...	178
Symbols and Definitions	...	Symbols and Definitions
Sympathetic retrogression	...	5.18	...	201
T
T-headed groynes. Demahy—	...	10.00 10.01	...	379 379
Tajewala tunnel-type excluder	...	6.24	...	267
Tando Mastikhan Fall. Remodelling of—	...	1.06	...	40
" " Fall. Variable coefficient of discharge of—	18.04	480
Tapti River	...	18.23	...	444
Technical. List of Annual Reports—	...	Appendix I	...	455
" List of Bombay—Papers	...	"	...	458
Temporary. Effect of—inflow of sand on regime	...	6.21	...	266
" Excess charge entering Mithrao Canal. Effect	12.03	408
Terminal velocity, charge, and grade—their effect on Area, velocity, slope, shape and width of a channel.	3.24	136
Terminal velocity (V_g) and charge (X) and their effect on Lacey formulae as modified by Sir Claude Ingles.	3.24	136
Terminology. Confusion due to lack of precision in—	...	Symbols and Defs.
Theorem. Bernoulli's—	...	11.00	...	387
Thickness of launched stone on slope	...	9.11	...	368
" " Stone—Kosi Bridge	...	9.11	...	368
" " " —Sarda "	...	9.11	...	368
Throw-off in vertically-exaggerated models. Incorrect—	18.33	447
Tidal models. Hooghly—	...	1.26	...	68
" " Rigid—	...	18.15, 18.16	...	441 441
" " Rupnarain—	...	1.26	...	73
" " Scale ratios of—	...	18.14	...	439
" " Semi-rigid—	...	18.17 to 18.20	...	441 to 442
" " Shoals and channels in—	...	18.14	...	439
Tilt. Definition of—	...	(viii)	...	5
Tilting of Naraj Weir	...	18.84	...	448
Time scale ratio	...	18.30	...	447
" scales different for scour and accretion	...	18.88	...	450
Terrinosity. Definition of—	...	(xi)	...	4
Training works considered anathema	...	12.01	...	407

INDEX

T, U, V and W.	Para. number.	Figure number.	Photo Sheet number.	Page number of Para.
Transported Solids on Rivers." Professor G. M. White's Paper of 1939 on "The Influence of—	8.11	102
Trimmu tunnel-type excluder	6.23 to 6.25	6-21 (a)	...	267 to 267
Tunnel-type ejectors	6.26 to 6.29	6-21 (a)	...	268 to 275
" " excluders (Eladen-Nicholson) Khanki, Kala bagh, Trimmu, Tajewala.	6.02, 6.23 to 6.25	219, 267 to 267
Turbulent flow. Reynold's criterion of—	13.12 to 13.18	439 to 439
U				
Unprecedented flood in Khari River in Ajmer-Merwara	12.05	409
Unsound to induce an excess charge to enter an off-take	12.03	403
V				
Vaghur at Raipur (C. P. and Berar). Maximum flood discharge in the—	12.05	409
" V=mean velocity	(iii)	2
V _s =terminal velocity. Definition of—	(xxvii)	8
V _w = \sqrt{gDB} (effect of shape and slope of channels on wave velocity.)	1-17	...
Valley. Recession of—	8.05	...	1-17	171
Vane. Effect of Left Bank attracting—near Rohri	1.11	46
" Submerged concave—for excluding sand	1.11, 6.16 to 6.17	1-11	...	46, 246 to 246
Vanes. King's—	6.18	6-18, 6-14	6-8	246
" Effect of adding splayed—at Tando Mastikhan Fall.	1.06	40
Vardha at Banwasi (C. P. & Berar). Maximum flood discharge in the—	12.05	409
Variable coefficient of discharge at Tando Mastikhan Fall	13.04	480
Variations in grade of bed material in the Eastern Nara Canal.	7.06	90
Variations in grade of bed material in the Rohri Canal	7.06	90
Velocity. Effect of shape of channel on wave—	1-17	...
Velocity terminal, charge and grade—their effect on Area velocity, slope, shape, and width of a channel.	8.24	186
Velocity terminal (V _s) and charge (X) and their effect on Lacey formulae as modified by Sir Claude Inglis.	8.24	186
Vernon-Harcourt	13.12	439
Vertical exaggeration. Definition of—	(ivii)	5
Vertically-exaggerated (A) tidal and (B) river models	13.12	439
" exaggerated mobile river models	13.23	444
" exaggerated rigid river models	13.21	448
" exaggerated. Scale ratios in—models	13.24 to 13.31	445 to 447
Vicksburg meander experiments	4.05	151
W				
W=a length characterising the effective width of an alluvial channel except where otherwise stated.	(iv)	2
W=surface width, or weight of a cu. ft. of water	(viii)	3
Watrap River (Kaira). Model of—	1.21	...	1-20	54
Wave relation V _w = \sqrt{gd} —Rayleigh's	13.14	439
White, G. M.'s discussion on Sir Claude Inglis' paper on "Meanders and their bearing on river training". Maritime and Waterways Paper No. 7, Inst. of C. E.	8.24	186
White, Professor G. M. Paper by—[1939] on "The Influence of transported solids on rivers."	8.11	102